

SNMP for EM316LNXNM-OT

Supplemental: Configuration and Reference



Fiber Driver Optical Multi-Service Platform

Published 2012/10/17 13:34:05

For EM316LNXNM v4.7 fdr 39 built Oct 16 2012 - 19:07:17

P/N 3010090-100 Revision B3 (-build r21138-)

User Guide

Three thick, parallel purple lines originate from a single point on the left and extend diagonally upwards towards the right, creating a sense of motion or expansion.

EMPOWERING
THE OPTICAL EDGE™

Copyright © 2012 MRV Communications, Inc.

All rights reserved.

No part of the contents of this document may be reproduced in any form or by any other means without written permission from the publisher.

Fiber Driver, Media Cross Connect, MegaVision, and other MRV product names and terms belong to MRV Communications or affiliates. All other brand names or trademarks referenced are the property of their respective owners.

This document includes electronic links and URLs that may require internet access. Some references may not be obvious on printed pages.

The user assumes sole responsibility for applying the information supplied in product documents.

MRV Communications reserves the right to make changes to technical specifications and documentation without notice.

This document represents the most recent product versions at the time of writing, which may differ from previous releases. To ensure maximum functionality, use the latest software updates and documents. Contact customer support regarding previous product revisions and documents.

Table of Contents

1. SNMP Management	1
1.1. Introduction	1
1.1.1. SNMP	1
1.1.2. In This Document	1
1.2. MIB Files	2
1.3. Object Name Convention	2
1.4. SNMP Enable and Disable	3
1.5. SNMPv1/v2c Setup	3
1.6. SNMPv3 Setup	5
1.7. SNMP Traps	6
1.8. SNMP and Trap Ports	7
1.9. UNIX Commands: Walk, Get, Set	8
1.10. Dynamic SNMP Information (MetaMIB)	9
1.10.1. Usage	9
1.10.2. Features Table	9
1.10.3. Dynamic Element Parameters	10
1.10.4. MetaMIB Objects (MCC ONLY)	11
1.10.5. Example MetaMIB Session - get	12
1.10.6. Example MetaMIB Session - set	13
2. SNMP References	14
2.1. SNMP Trap Reference	14
2.1.1. nbsCmmcTrapDeviceRebooted	14
2.1.2. nbsCmmcTrapDeviceOnline	14
2.1.3. nbsCmmcTrapDeviceShuttingDown	14
2.1.4. nbsCmmcTrapPowerSupplyFailure	15
2.1.5. nbsCmmcTrapPowerSupplyRestored	15
2.1.6. nbsCmmcTrapFanFailure	16
2.1.7. nbsCmmcTrapFanRestored	16
2.1.8. nbsCmmcTrapChassisTooHot	16
2.1.9. nbsCmmcTrapChassisTooCold	17
2.1.10. nbsCmmcTrapChassisTempOk	17
2.1.11. nbsCmmcTrapSlotModuleIn	18
2.1.12. nbsCmmcTrapSlotModuleOut	18
2.1.13. nbsCmmcTrapPortEnabled	19
2.1.14. nbsCmmcTrapPortDisabled	20
2.1.15. nbsCmmcTrapPortLinkUp	20
2.1.16. nbsCmmcTrapPortLinkDown	21
2.1.17. nbsCmmcTrapPortLINOn	21
2.1.18. nbsCmmcTrapPortLINOOff	22
2.1.19. nbsCmmcTrapPortLoopbackOn	22
2.1.20. nbsCmmcTrapPortLoopbackOff	23
2.1.21. nbsCmmcTrapPortMaximumExceeded	23
2.1.22. nbsCmmcTrapPortRemoved	24
2.1.23. nbsCmmcTrapPortInserted	25
2.1.24. nbsCmmcTrapPortTempTooLow	26
2.1.25. nbsCmmcTrapPortTempTooHigh	27
2.1.26. nbsCmmcTrapPortRxPowerTooLow	28
2.1.27. nbsCmmcTrapPortRxPowerTooHigh	29
2.1.28. nbsCmmcTrapPortTxPowerTooLow	30
2.1.29. nbsCmmcTrapPortTxPowerTooHigh	31
2.1.30. nbsCmmcTrapPortAmpsTooLow	32

2.1.31. nbsCmmcTrapPortAmpsTooHigh	33
2.1.32. nbsCmmcTrapPortVoltsTooLow	34
2.1.33. nbsCmmcTrapPortVoltsTooHigh	35
2.1.34. nbsCmmcTrapSwitchover	36
2.1.35. nbsCmmcTrapSlotShuttingDown	37
2.1.36. nbsCmmcTrapPortCrcError	38
2.1.37. nbsCmmcTrapCpeInManagedChassis	38
2.1.38. nbsCmmcTrapCoWithoutCpe	39
2.1.39. nbsCmmcTrapCoTakesControl	39
2.1.40. nbsCmmcTrapCoYieldsControl	40
2.1.41. nbsCmmcTrapCoLinkedToCo	40
2.1.42. nbsCmmcTrapCpeFound	40
2.1.43. nbsCmmcTrapPortReflectionDetected	41
2.1.44. nbsCmmcTrapPortReflectionCeased	41
2.1.45. nbsCmmcTrapPortTempOk	42
2.1.46. nbsCmmcTrapPortRxPowerOk	43
2.1.47. nbsCmmcTrapPortTxPowerOk	43
2.1.48. nbsCmmcTrapPortAmpsOk	44
2.1.49. nbsCmmcTrapPortVoltsOk	44
2.1.50. nbsCmmcTrapSlotTempTooLow	45
2.1.51. nbsCmmcTrapSlotTempTooHigh	45
2.1.52. nbsCmmcTrapSlotTempOk	46
2.1.53. nbsCmmcTrapPortErrorsDetected	46
2.1.54. nbsCmmcTrapPortErrorsStopped	47
2.1.55. nbsCmmcTrapChassisInsufficientPower	48
2.1.56. nbsCmmcTrapChassisSufficientPower	48
2.1.57. nbsCmmcTrapSlotModuleLocked	48
2.1.58. nbsCmmcTrapSelectLinkChanged	49
2.1.59. nbsOsaTrapPortChannelAdded	50
2.1.60. nbsOsaTrapPortChannelDropped	50
2.1.61. nbsOsaTrapPortRxPowerTooLow	51
2.1.62. nbsOsaTrapPortRxPowerOK	52
2.1.63. nbsOsaTrapPortRxPowerTooHigh	53
2.1.64. nbsOsaTrapPortOSNRTooLow	53
2.1.65. nbsOsaTrapPortOSNR0K	54
2.1.66. nbsOsaTrapPortOSNRTooHigh	55
2.1.67. nbsMccLinkToggleTrapStart	55
2.1.68. nbsMccLinkToggleTrapStop	56
2.1.69. nbsPrbsTrapGeneratorStarted	56
2.1.70. nbsPrbsTrapGeneratorStopped	56
2.1.71. nbsPrbsTrapCheckerStarted	57
2.1.72. nbsPrbsTrapCheckerStopped	57
2.1.73. nbsPrbsTrapCheckerOverflowed	58
2.1.74. nbsPrbsTrapCheckerErrorDetected	58
2.1.75. nbsPrbsTrapCheckerStatusUpdate	59
2.1.76. nbsPrbsTrapCheckerSyncIn	60
2.1.77. nbsPrbsTrapCheckerSyncOut	61
2.2. SNMP Set Reference	63
2.2.1. Configuration SNMP MIB Object CLI Reference	63
2.2.2. Chassis SNMP MIB Object CLI Reference	64
2.2.3. Slot SNMP MIB Object CLI Reference	65
2.2.4. Port SNMP MIB Object CLI Reference	66
.....	69

List of Tables

2.1. nbsCmmcTrapDeviceRebooted Enables	14
2.2. nbsCmmcTrapDeviceRebooted Variables	14
2.3. nbsCmmcTrapDeviceOnline Enables	14
2.4. nbsCmmcTrapDeviceOnline Variables	14
2.5. nbsCmmcTrapDeviceShuttingDown Enables	15
2.6. nbsCmmcTrapDeviceShuttingDown Variables	15
2.7. nbsCmmcTrapPowerSupplyFailure Enables	15
2.8. nbsCmmcTrapPowerSupplyFailure Variables	15
2.9. nbsCmmcTrapPowerSupplyRestored Enables	15
2.10. nbsCmmcTrapPowerSupplyRestored Variables	15
2.11. nbsCmmcTrapFanFailure Enables	16
2.12. nbsCmmcTrapFanFailure Variables	16
2.13. nbsCmmcTrapFanRestored Enables	16
2.14. nbsCmmcTrapFanRestored Variables	16
2.15. nbsCmmcTrapChassisTooHot Enables	17
2.16. nbsCmmcTrapChassisTooHot Variables	17
2.17. nbsCmmcTrapChassisTooCold Enables	17
2.18. nbsCmmcTrapChassisTooCold Variables	17
2.19. nbsCmmcTrapChassisTempOk Enables	18
2.20. nbsCmmcTrapChassisTempOk Variables	18
2.21. nbsCmmcTrapSlotModuleIn Enables	18
2.22. nbsCmmcTrapSlotModuleIn Variables	18
2.23. nbsCmmcTrapSlotModuleOut Enables	19
2.24. nbsCmmcTrapSlotModuleOut Variables	19
2.25. nbsCmmcTrapPortEnabled Enables	19
2.26. nbsCmmcTrapPortEnabled Variables	19
2.27. nbsCmmcTrapPortDisabled Enables	20
2.28. nbsCmmcTrapPortDisabled Variables	20
2.29. nbsCmmcTrapPortLinkUp Enables	20
2.30. nbsCmmcTrapPortLinkUp Variables	20
2.31. nbsCmmcTrapPortLinkDown Enables	21
2.32. nbsCmmcTrapPortLinkDown Variables	21
2.33. nbsCmmcTrapPortLINOn Enables	21
2.34. nbsCmmcTrapPortLINOn Variables	22
2.35. nbsCmmcTrapPortLINOOff Enables	22
2.36. nbsCmmcTrapPortLINOOff Variables	22
2.37. nbsCmmcTrapPortLoopbackOn Enables	23
2.38. nbsCmmcTrapPortLoopbackOn Variables	23
2.39. nbsCmmcTrapPortLoopbackOff Enables	23
2.40. nbsCmmcTrapPortLoopbackOff Variables	23
2.41. nbsCmmcTrapPortMaximumExceeded Enables	24
2.42. nbsCmmcTrapPortMaximumExceeded Variables	24
2.43. nbsCmmcTrapPortRemoved Enables	24
2.44. nbsCmmcTrapPortRemoved Variables	25
2.45. nbsCmmcTrapPortInserted Enables	25
2.46. nbsCmmcTrapPortInserted Variables	25
2.47. nbsCmmcTrapPortTempTooLow Enables	26
2.48. nbsCmmcTrapPortTempTooLow Variables	26
2.49. nbsCmmcTrapPortTempTooHigh Enables	27
2.50. nbsCmmcTrapPortTempTooHigh Variables	27
2.51. nbsCmmcTrapPortRxFPowerTooLow Enables	28

2.52. nbsCmmcTrapPortRxPowerTooLow Variables	28
2.53. nbsCmmcTrapPortRxPowerTooHigh Enables	29
2.54. nbsCmmcTrapPortRxPowerTooHigh Variables	29
2.55. nbsCmmcTrapPortTxPowerTooLow Enables	30
2.56. nbsCmmcTrapPortTxPowerTooLow Variables	30
2.57. nbsCmmcTrapPortTxPowerTooHigh Enables	31
2.58. nbsCmmcTrapPortTxPowerTooHigh Variables	31
2.59. nbsCmmcTrapPortAmpsTooLow Enables	32
2.60. nbsCmmcTrapPortAmpsTooLow Variables	32
2.61. nbsCmmcTrapPortAmpsTooHigh Enables	33
2.62. nbsCmmcTrapPortAmpsTooHigh Variables	33
2.63. nbsCmmcTrapPortVoltsTooLow Enables	34
2.64. nbsCmmcTrapPortVoltsTooLow Variables	34
2.65. nbsCmmcTrapPortVoltsTooHigh Enables	35
2.66. nbsCmmcTrapPortVoltsTooHigh Variables	36
2.67. nbsCmmcTrapSwitchover Enables	37
2.68. nbsCmmcTrapSwitchover Variables	37
2.69. nbsCmmcTrapSlotShuttingDown Enables	37
2.70. nbsCmmcTrapSlotShuttingDown Variables	37
2.71. nbsCmmcTrapPortCrcError Enables	38
2.72. nbsCmmcTrapPortCrcError Variables	38
2.73. nbsCmmcTrapCpeInManagedChassis Enables	38
2.74. nbsCmmcTrapCpeInManagedChassis Variables	38
2.75. nbsCmmcTrapCoWithoutCpe Enables	39
2.76. nbsCmmcTrapCoWithoutCpe Variables	39
2.77. nbsCmmcTrapCoTakesControl Enables	39
2.78. nbsCmmcTrapCoTakesControl Variables	39
2.79. nbsCmmcTrapCoYieldsControl Enables	40
2.80. nbsCmmcTrapCoYieldsControl Variables	40
2.81. nbsCmmcTrapCoLinkedToCo Enables	40
2.82. nbsCmmcTrapCoLinkedToCo Variables	40
2.83. nbsCmmcTrapCpeFound Enables	41
2.84. nbsCmmcTrapCpeFound Variables	41
2.85. nbsCmmcTrapPortReflectionDetected Enables	41
2.86. nbsCmmcTrapPortReflectionDetected Variables	41
2.87. nbsCmmcTrapPortReflectionCeased Enables	42
2.88. nbsCmmcTrapPortReflectionCeased Variables	42
2.89. nbsCmmcTrapPortTempOk Enables	42
2.90. nbsCmmcTrapPortTempOk Variables	42
2.91. nbsCmmcTrapPortRxPowerOk Enables	43
2.92. nbsCmmcTrapPortRxPowerOk Variables	43
2.93. nbsCmmcTrapPortTxPowerOk Enables	43
2.94. nbsCmmcTrapPortTxPowerOk Variables	43
2.95. nbsCmmcTrapPortAmpsOk Enables	44
2.96. nbsCmmcTrapPortAmpsOk Variables	44
2.97. nbsCmmcTrapPortVoltsOk Enables	45
2.98. nbsCmmcTrapPortVoltsOk Variables	45
2.99. nbsCmmcTrapSlotTempTooLow Enables	45
2.100. nbsCmmcTrapSlotTempTooLow Variables	45
2.101. nbsCmmcTrapSlotTempTooHigh Enables	46
2.102. nbsCmmcTrapSlotTempTooHigh Variables	46
2.103. nbsCmmcTrapSlotTempOk Enables	46
2.104. nbsCmmcTrapSlotTempOk Variables	46
2.105. nbsCmmcTrapPortErrorsDetected Enables	47

2.106. nbsCmmcTrapPortErrorsDetected Variables	47
2.107. nbsCmmcTrapPortErrorsStopped Enables	47
2.108. nbsCmmcTrapPortErrorsStopped Variables	47
2.109. nbsCmmcTrapChassisInsufficientPower Enables	48
2.110. nbsCmmcTrapChassisInsufficientPower Variables	48
2.111. nbsCmmcTrapChassisSufficientPower Enables	48
2.112. nbsCmmcTrapChassisSufficientPower Variables	48
2.113. nbsCmmcTrapSlotModuleLocked Enables	49
2.114. nbsCmmcTrapSlotModuleLocked Variables	49
2.115. nbsCmmcTrapSelectLinkChanged Enables	49
2.116. nbsCmmcTrapSelectLinkChanged Variables	49
2.117. nbsOsaTrapPortChannelAdded Enables	50
2.118. nbsOsaTrapPortChannelAdded Variables	50
2.119. nbsOsaTrapPortChannelDropped Enables	51
2.120. nbsOsaTrapPortChannelDropped Variables	51
2.121. nbsOsaTrapPortRxPowerTooLow Enables	51
2.122. nbsOsaTrapPortRxPowerTooLow Variables	51
2.123. nbsOsaTrapPortRxPowerOK Enables	52
2.124. nbsOsaTrapPortRxPowerOK Variables	52
2.125. nbsOsaTrapPortRxPowerTooHigh Enables	53
2.126. nbsOsaTrapPortRxPowerTooHigh Variables	53
2.127. nbsOsaTrapPortOSNRTooLow Enables	53
2.128. nbsOsaTrapPortOSNRTooLow Variables	54
2.129. nbsOsaTrapPortOSNR0K Enables	54
2.130. nbsOsaTrapPortOSNR0K Variables	54
2.131. nbsOsaTrapPortOSNRTooHigh Enables	55
2.132. nbsOsaTrapPortOSNRTooHigh Variables	55
2.133. nbsMccLinkToggleTrapStart Enables	55
2.134. nbsMccLinkToggleTrapStart Variables	56
2.135. nbsMccLinkToggleTrapStop Enables	56
2.136. nbsMccLinkToggleTrapStop Variables	56
2.137. nbsPrbsTrapGeneratorStarted Enables	56
2.138. nbsPrbsTrapGeneratorStarted Variables	56
2.139. nbsPrbsTrapGeneratorStopped Enables	57
2.140. nbsPrbsTrapGeneratorStopped Variables	57
2.141. nbsPrbsTrapCheckerStarted Enables	57
2.142. nbsPrbsTrapCheckerStarted Variables	57
2.143. nbsPrbsTrapCheckerStopped Enables	57
2.144. nbsPrbsTrapCheckerStopped Variables	57
2.145. nbsPrbsTrapCheckerOverflowed Enables	58
2.146. nbsPrbsTrapCheckerOverflowed Variables	58
2.147. nbsPrbsTrapCheckerErrorDetected Enables	59
2.148. nbsPrbsTrapCheckerErrorDetected Variables	59
2.149. nbsPrbsTrapCheckerStatusUpdate Enables	59
2.150. nbsPrbsTrapCheckerStatusUpdate Variables	59
2.151. nbsPrbsTrapCheckerSyncIn Enables	60
2.152. nbsPrbsTrapCheckerSyncIn Variables	60
2.153. nbsPrbsTrapCheckerSyncOut Enables	61
2.154. nbsPrbsTrapCheckerSyncOut Variables	61
2.155. Configuration Table	63
2.156. Chassis Table	64
2.157. Slot Table	65
2.158. Port Table	66

Chapter 1. SNMP Management

...introduction to SNMP setup

1.1. Introduction

1.1.1. SNMP

Simple Network Management Protocol (SNMP) is an industry standard application layer protocol used for monitoring and controlling network devices. SNMP is built on the UDP transport protocol, which is efficient but does not inherently guarantee packet delivery. However, newer SNMP v3 includes some reliable messaging with acknowledgements.

SNMP typically uses a software "agent" at each managed device to collect and share information about the device on the network. Some devices have capabilities that may also be remotely controlled through the agent software by SNMP commands. Network management systems (NMS) such as MRV's MegaVision can collect information from these standard SNMP agents throughout a network.

The Fiber Driver product line from MRV Communications uses a network management module to connect each manageable network node (chassis) to an IP network. The EM316LNXNM-OT (LNXNM-OT) is a plug-and-play management device that begins operating when the host chassis is powered on and connected to the network. It provides a command line interface (CLI) as well as SNMP support to enhance the functionality of networking modules in the host chassis. To ensure proper operation specific to your network configuration and to provide SNMP access, some initial environment-specific parameters must be configured through the CLI. Refer to LNXNM-OT documentation for setup and operation details.

The LNXNM-OT is designed specifically for the Fiber Driver product line. The module includes two SFP ports for additional network access options.

1.1.2. In This Document

This manual covers SNMP access to the LNXNM-OT management module through management information base (MIB) files. Two of these MIBs are specific to Fiber Driver and discussed in this document. The first MIB file is static, which has always been supported by MRV. The objects in the MIB file (see below) allow configuration of common features of the LNXNM-OT management module. The second "MetaMIB" file provides objects to configure the LNXNM-OT features not accessed by the MIB file objects. The main difference between static and dynamic SNMP is the number of objects returned to the user. Using static SNMP, each MIB object corresponds directly with an object in the chassis. In contrast, the MetaMIB only keeps track of hardware elements (chassis, slot, or port) that support specific objects. The MetaMIB limits excess unsupported objects returned to the user.

1.2. MIB Files

Management Information Base (MIB) structure and values are defined in files for Fiber Driver and MegaVision. The file names are shown in the table below:

	Main MIB	Meta MIB
Fiber Driver	cmmc.mib	nbs-meta.mib
MegaVision	cmmc.mib	nbs-meta.mib

The name of the MIB file is not important; all files in the MIB directory are used.

To ensure the best SNMP access, use the MIB files provided for the specific software release used in your system.

MIB files may be obtained through MRV customer support (<http://service.mrv.com/support/index.cfm>). Email and phone contact information is provided at <http://www.mrv.com> and in the product manuals.

1.3. Object Name Convention

The SNMP traps begin with the common string "nbsCmmc" for historical MRV product support. This convention is not expected to change.

1.4. SNMP Enable and Disable

Users can enable and disable SNMP v1/v2c/v3 agents using the following commands:

Enable

- **"snmp-server (v1|v2c|v3)"**

Disable

- **"no snmp-server (v1|v2c|v3)"**

For improved security, turn off SNMP v1 and v2c. Also, always change the community strings from the default values.

1.5. SNMPv1/v2c Setup

1. Set up the SNMP community strings for read and write access using the commands shown below. For security reasons, the **"show"** commands do not display the community strings. Community strings are encrypted in the **"show running-config"** command for security. The default community strings for "read" and "write" are **public** and **private**, respectively.

```
fiberdriver(config)# snmp-server community read readSecret
fiberdriver(config)# snmp-server community write writeSecret
fiberdriver(config)#
```

2. Configure the SNMP trap receiver table. Add the IP addresses of each network manager station that should receive traps from the SNMP agent.

```
fiberdriver(config)# snmp-server host 169.254.192.117
fiberdriver(config)# show snmp-server hosts
snmp-server host 169.254.192.117 public warning
fiberdriver(config)#
```

3. SNMP traps are sent to address listed in the trap receiver table. Each receiving device must include management capabilities to interpret SNMP traps. MRV recommends MegaVision, which includes special support for Fiber Driver graphical management. In MegaVision, open the trap receiver table with the "System-->IP/SNMP Configuration" menu selection. SNMP traps are sent to network management systems (NMS) like MegaVision that support SNMP. SNMP NMS IP addresses are entered into the traps table through the "System —> IP/SNMP Configuration" windows in MegaVision.
4. Some example traps from the EM316LNxNM are listed below:
 - Chassis temperature outside pre-determined safe operational limits
 - Power supply failure
 - Fan failure (certain chassis)
 - Hardware or software malfunctions
 - Informational occurrences (module specific)
 - Change in link status (link up, link down)
 - Change in slot inventory (module removed or inserted)

- Change in port inventory (pluggable port removed or inserted)

For a complete list, see the [SNMP Trap Reference](#) section.

5. Completely disable trap generation by removing all IP addresses from the SNMP trap table:

```
fiberdriver(config)# no snmp-server host
fiberdriver(config)#
```

Selectively disable specific traps types with the "**no gen-trap**" command, found in the chassis 1 config context:

```
fiberdriver(chassis/1)# no gen-trap chassis
fiberdriver(chassis/1)# no gen-trap lin
fiberdriver(chassis/1)# no gen-trap link
fiberdriver(chassis/1)# no gen-trap loopback
fiberdriver(chassis/1)# show
    Model: EM316-16BU
    Name: EM316-16
    Temp(C): 23
    Temp Min(C): 5
    Temp Limit(C): 50

PS1: DC Bad
PS2: AC Good

Fan1: good  Fan3: good
Fan2: good  Fan4: not Installed

Chassis Traps: off  Slot Change Traps: on  Module Specific Traps: on
  Port Traps: on      Link Traps: off      Loopback Traps: off
    LIN Traps: off  Port Change Traps: on      Port Diags Traps: on

Number Of Slots: 16

Slot  Model          Name
====  =====
1.3   EM316-LNXNM12  Slot 1 (EM316-LNXNM12 at 1.3)
fiberdriver(chassis/1)#
```

1.6. SNMPv3 Setup

(This section assumes familiarity with SNMPv3 concepts.)

You can create an SNMPv3 user with authentication ("auth") or authentication+privilege ("auth/priv") level security.

Use "**snmp-server user**" commands to create the users.

You can use MegaVision SNMPv3 features to communicate with the device. The passwords used in user creation must be at least 8 characters long. SNMPv3 passwords are stored encrypted. The LNXNM MAC address (which is different for every NM) is used to encrypt the passwords. For this reason, it is required to recreate the SNMPv3 passwords when a configuration file containing SNMPv3 passwords is moved from one NM to another NM.

Example: The following commands create some SNMPv3 users.

```
fiberdriver(config)# snmp-server user fdrNoAuth
fiberdriver(config)# snmp-server user fdrMd5Auth auth md5 open-sesame
fiberdriver(config)# snmp-server user fdrMd5Priv auth md5 open-sesame priv
des close-sesame
fiberdriver(config)# snmp-server user fdrShaAuth auth sha open-sesame
fiberdriver(config)# snmp-server user fdrShaPriv auth sha open-sesame priv
des close-sesame
fiberdriver(config)#
```

In the above commands, "*open-sesame*" and "*close-sesame*" are passwords and usernames start with "fdr".

Authentication may be set to MD5 or SHA. Privacy may be set to DES only.

1.7. SNMP Traps

The LNXNM can display log messages to a CLI terminal, send syslog messages, and send SNMP traps in response to certain conditions detected by the system. The default sensitivity levels for message logging (shown below) are sufficient for normal operation.

```
fiberdriver(config)# log level trap ?
  alarm      Set log threshold to alarm - similar to LOG_warning (4)
  error      Set log threshold to LOG_ERR (3)
  fatal       Set log threshold to LOG_EMERG (0)
  warning    Set log threshold to LOG_WARNING (4)
fiberdriver(config)# log level trap
```

An event can cause an SNMP trap to one or more remote SNMP managers, which allows a network administrator to receive immediate error notification. To specify an SNMP trap manager address, use the **"snmp-server host"** command. To change the default setting for trap message level, use the **"log level trap"** command.

```
fiberdriver(config)# snmp-server host 169.254.1.100
fiberdriver(config)# snmp-server host 169.254.1.101
fiberdriver(config)# show snmp-server hosts
snmp-server host 169.254.1.100 public warning
snmp-server host 169.254.1.101 public warning

fiberdriver(config)# log level trap error
fiberdriver(config)# show log
Running Level: info
Nvram Level: disabled
Trap Level: error
Email Level: disabled
Remote Server: 0.0.0.0
Remote Level: memo
fiberdriver(config)#
```

"info" and **"memo"** levels are not available for traps. **"warning"** is the lowest priority available for traps.

1.8. SNMP and Trap Ports

The default network port for SNMP **get** or **set** is 161. The default SNMP trap port is 162. These ports may be changed to resolve system configuration conflicts or to improve security.

```
fiberdriver(config)# snmp-server port 150
fiberdriver(config)# snmp-server trap-port 140

fiberdriver(config)# show snmp-server
Administrative configuration:
  Snmp V1: disabled
  Snmp V2c: disabled
  Snmp V3: disabled
  Power Supply Traps: enabled
  Module Traps: enabled
  Snmp Port desired: 150
  Trap Port desired: 140
  SysContact:
  SysName:
  SysLocation:
Current operating configuration:
  Snmp Port: 161
  Trap Port: 162
fiberdriver(config)#
```

In the example above, note that the "Snmp Port desired" changes to the values from the commands issued a few lines above. These changes are not active until system changes are written to the configuration file.

The "Current operating configuration" values keep the previous values until the changes are saved and the system is restarted as shown below:

```
fiberdriver(config)# write file
fiberdriver(config)# exit
fiberdriver# restart warm
```

After restarting, the desired ports listed above become the active ports as shown below:

```
fiberdriver# show snmp-server
Administrative configuration:
  Snmp V1: disabled
  Snmp V2c: disabled
  Snmp V3: disabled
  Power Supply Traps: enabled
  Module Traps: enabled
  Snmp Port desired: 150
  Trap Port desired: 140
  SysContact:
  SysName:
  SysLocation:
Current operating configuration:
  Snmp Port: 150
  Trap Port: 140
fiberdriver#
```

1.9. UNIX Commands: Walk, Get, Set

The following examples illustrate the basic **get**, **set**, and **walk** commands for SNMP in the UNIX (Linux) environment. Use the MIB file appropriate to your application. (see section "MIB Files" above)

```
$ snmpget -c public -m ./cmmc.mib 192.168.14.201
nbsCmmcPortZoneIfIndexAdmin.1.2.1

NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexAdmin.1.2.1 = INTEGER: 102002
```

```
$ snmpset -c private -m ./cmmc.mib 192.168.14.201
nbsCmmcPortZoneIfIndexAdmin.1.2.1 i 102003

NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexAdmin.1.2.1 = INTEGER: 102003
```

```
$ snmpwalk -c public -m ./cmmc.mib 192.168.14.201 .

NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.1 = INTEGER: 101002
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.2 = INTEGER: 101001
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.3 = INTEGER: 101004
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.4 = INTEGER: 101003
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.5 = INTEGER: 101006
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.6 = INTEGER: 101005
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.7 = INTEGER: 101008
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.8 = INTEGER: 101007
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.9 = INTEGER: 101010
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.10 = INTEGER: 101009
NBS-CMMC-MIB::nbsCmmcPortZoneIfIndexOper.1.1.11 = INTEGER: 101012
    Too much to show
```

** The output for the **walk** command above is truncated because the full display is too long for this printed format.**

1.10. Dynamic SNMP Information (MetaMIB)

The MetaMIB is an extension to the MIB architecture used by the Fiber Driver. Instead of relying on static objects, the MetaMIB dynamically builds objects for the system.

1.10.1. Usage

The Meta-MIB is not included in the standard MIB "cmmc.mib" file. It is in the file named "nbs-meta.mib". The Meta-MIB requires that the MIB search path always includes the standard MIB.

The MetaMIB is divided into two portions. The first portion includes the available features covered by the MetaMIB. The second portion includes MetaMIB usage on the Fiber Driver system in use.

1.10.2. Features Table

MetaMIB Object	Description
metaMibFeatureTableSize	Returns how many MetaMIB features are available.
metaMibFeatureID.X	Returns the ID of MetaMIB feature X.
metaMibFeatureFamily.X	Returns what family MetaMIB feature X is a part of.
metaMibFeatureName.X	Returns what name MetaMIB feature X uses.
metaMibFeatureDesc.X	Returns the full description of MetaMIB feature X.
metaMibFeatureUnits.X	Returns the type of unit MetaMIB feature X uses. (optional)
metaMibFeatureType.X	Returns the MetaMIB feature type: • Enumeration • String • Octet String • Integer • Float
metaMibFeatureOID.X	Returns a unique ID string for this feature. This remains fixed for the life of the product.

In the table above there is a variable X which refers to a specific feature. When traversing the metaMibFeature* table, you can tie together a features attributes by using the .X notation. For example to get feature #10's name and description, use metaMibFeatureName.10 and metaMibFeatureDesc.10.

1.10.3. Dynamic Element Parameters

MetaMIB Object	Description
metaMibVariableTableSize	Returns how many MetaMIB objects currently in use on the Fiber Driver
metaMibVariableIfIndex.X.Y	Returns the interface index: X
metaMibVariableID.X.Y	Returns the MetaMIB object ID (Y) used in the features table for this variable object
metaMibVariableCaps.X.Y	Returns a list of comma separated strings that indicate the type of values this variable supports. Ranges and string lengths are expressed as a two item list: MIN, MAX. A zero length string indicates that this variable is read-only.
metaMibVariableDefault.X.Y	Returns the default value of this variable.
metaMibVariableJumper.X.Y	Returns the jumper settings of this variable. If the object does not have a jumper for this feature: • It will report 'N/A' if metaMibVariableType is string. • It will be zero length otherwise. When read, a zero length string is valid if Type is string. Note this is not used by the Media Cross Connect.
metaMibVariableOper.X.Y	Returns the current operational value for this variable. If the object cannot report the current operational value: • It will report 'N/A' if metaMibVariableType is string. • It will be zero length otherwise. • If Caps reports non-zero length, this variable is write-only due to hardware limitations. When read, a zero length string is valid if Type is string.
metaMibVariableAdmin.X.Y	Returns the current administrative value of this variable. If the Administrative value cannot be set for this variable, Caps is zero-length and it reports a zero length string. Writing zero length values is rejected unless Type is string and Caps permits it. When read, a zero length string is valid if Type is string.
metaMibVariableStatus.X.Y	Returns any messages relating to this variable.

In the preceeding table, X is the interface index of a port in the form CSSPPP. C is the chassis number, SS is the 2-digit slot number (00-10), and PPP is the 3-digit port number (000-100). To target a slot, the PPP field should be empty. To target a chassis, both the SS and the PPP fields should be empty. For example, index notation for port 1.2.3 is 102003 and slot 1.2 is 102000.

In the preceeding table, Y is the element's feature ID. For example, if the MetaMIB object ends with 102003.12 then the port 1.2.3 has feature ID #12.

1.10.4. MetaMIB Objects (MCC ONLY)

Currently the Media Cross Connect product line uses only a few MetaMIB objects.

The first set of objects are part of the "Voltage Monitor" family and have to do with voltage readings on the back plane of the new NC316-144PMC-8X chassis:

1. Voltage Slot 1 (metaMibFeatureOID = 3.1.0)
2. Voltage Backplane & Slot 2 (metaMibFeatureOID = 3.1.1)
3. Voltage Slot 3 (metaMibFeatureOID = 3.1.2)
4. Voltage Slot 4 (metaMibFeatureOID = 3.1.3)
5. Voltage NM (metaMibFeatureOID = 3.1.4)

The second set of objects are part of the "SATA/SAS Cu SFP" family for configuring the SFP-SATA-SAS-HT and SFP-SATA-SAS-DR SFPs:

1. Equalization (metaMibFeatureOID = 1.1.0)
2. De-emphasis (metaMibFeatureOID = 1.2.0)
3. Swing (metaMibFeatureOID = 1.3.0)

The third set of objects are part of the "Fiber Config on RJ45 Port" family for configuring fiber options on the EMPMC-36RJ-C blade:

1. Fiber Mode (metaMibFeatureOID = 1.5.0)
2. Fiber Speed (metaMibFeatureOID = 1.5.1)
3. Fiber Auto-Negotiation (metaMibFeatureOID = 1.5.2)

1.10.5. Example MetaMIB Session - get

First, do an SNMP walk on the entire Fiber Driver being used. From there, find the object that you wish to configure. For simplicity, use the "metaMibFeatureOID" of your target object to find the ID for configuration. For example, to find the equalization value on an SFP-SATA-SAS-HT SFP, search for "metaMibFeatureOID" that is set to 1.1.0.

Below is a truncated version of an SNMP walk on a chassis focusing on the equalization feature; other features are ignored.

```
$ snmpwalk -c public -v 1 -m ./nbs-meta.mib 192.168.14.201 metaMib
NBS-META-MIB::metaMibFeatureTableSize.0 = INTEGER: 24
NBS-META-MIB::metaMibFeatureID.11 = Gauge32: 11
NBS-META-MIB::metaMibFeatureFamily.11 = STRING: SATA/SAS Cu SFP
NBS-META-MIB::metaMibFeatureName.11 = STRING: Equalization
NBS-META-MIB::metaMibFeatureDesc.11 = STRING: Input Equalization
NBS-META-MIB::metaMibFeatureUnits.11 = STRING:
NBS-META-MIB::metaMibFeatureType.11 = INTEGER: enum(1)
NBS-META-MIB::metaMibFeatureOID.11 = STRING: 1.1.0
NBS-META-MIB::metaMibVariableTableSize.0 = INTEGER: 8
NBS-META-MIB::metaMibVariableIfIndex.104001.11 = Gauge32: 104001
NBS-META-MIB::metaMibVariableID.104001.11 = Gauge32: 11
NBS-META-MIB::metaMibVariableCaps.104001.11 = STRING: disabled, low, medium, high
NBS-META-MIB::metaMibVariableDefault.104001.11 = STRING: disabled
NBS-META-MIB::metaMibVariableJumper.104001.11 = STRING:
NBS-META-MIB::metaMibVariableOper.104001.11 = STRING:
NBS-META-MIB::metaMibVariableAdmin.104001.11 = STRING: disabled
NBS-META-MIB::metaMibVariableStatus.104001.11 = STRING:
```

The line "NBS-META-MIB::metaMibFeatureOID.11 = STRING: 1.1.0" gives us what we need. We match 1.1.0 with feature 11. Now in the metaMibVariable* section we can use CSSPPP.11 to find all of the relevant information on equalization.

To get specific information on a port, use the relevant MIB object (in the current example, we can use #11) on a port with the desired feature. For example to just get the administrative status of equalization on port 1.4.1 use the example below.

```
$ snmpget -c public -v 1 -m ./nbs-meta.mib 192.168.14.201
metaMibVariableAdmin.104001.11
NBS-META-MIB::metaMibVariableAdmin.104001.11 = STRING: disabled
```

1.10.6. Example MetaMIB Session - set

It is suggested to follow the steps in the previous section to figure out what objects are available to be changed on the system. After figuring out which object to configure, use the MetaMIB object "metaMibVariableAdmin" to change the value.

For example using the equalization object from the previous section, we can change the value from "disabled" to "medium". We know "medium" is an available option by looking at what was returned from "metaMibVariableCaps.104001.11" and "metaMibFeatureType.11". The values returned were "disabled, low, medium and high" and "enum" respectively. This means the MetaMIB object is an enumeration with the available options: disabled, low, medium and high.

```
$ snmpset -c private -v 1 -m ./nbs-meta.mib 192.168.14.201
metaMibVariableAdmin.104001.11 s medium
NBS-META-MIB::metaMibVariableAdmin.104001.11 = STRING: medium
```

Chapter 2. SNMP References

2.1. SNMP Trap Reference

2.1.1. nbsCmmcTrapDeviceRebooted

Sent after device boots up. The cause of the last shutdown is indicated in nbsCmmmcTrapShutdownReason. This Notification should be of Severity FATAL.

Log message format: Device Rebooted, Shutdown Reason:
 <ShutdownReason>

Table 2.1. nbsCmmcTrapDeviceRebooted Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.2. nbsCmmcTrapDeviceRebooted Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>TrapShutdownReason</i>	The reason for the last system shutdown

2.1.2. nbsCmmcTrapDeviceOnline

Sent when device detects restoration of network communications. This Notification should be of Severity **WARNING**.

Log message format: Device Online

Table 2.3. nbsCmmcTrapDeviceOnline Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.4. nbsCmmcTrapDeviceOnline Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system

2.1.3. nbsCmmcTrapDeviceShuttingDown

Sent just before device shuts itself down. Reason for shutdown is indicated in nbsCmmcTrapShutdownReason. This Notification should be of Severity FATAL.

Log message format: Device Shutting Down, Shutdown Reason:
 <ShutdownReason>

Table 2.5. nbsCmmcTrapDeviceShuttingDown Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.6. nbsCmmcTrapDeviceShuttingDown Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>TrapShutdownReason</i>	The reason for the last system shutdown

2.1.4. nbsCmmcTrapPowerSupplyFailure

Unique trap for power supply failure events. This Notification should be of Severity ERROR.

Log message format: Chassis x Power Supply Failure, Power Supply Id:
 <PowerSupplyId>

Table 2.7. nbsCmmcTrapPowerSupplyFailure Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.8. nbsCmmcTrapPowerSupplyFailure Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>TrapPowerSupplyId</i>	ID of the power supply
<i>ChassisName</i>	The user assigned name for this chassis

2.1.5. nbsCmmcTrapPowerSupplyRestored

Sent when power supply starts working again. This Notification should be of Severity ERROR.

Log message format: Chassis x Power Supply Restored, Power Supply Id:
 <PowerSupplyId>

Table 2.9. nbsCmmcTrapPowerSupplyRestored Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.10. nbsCmmcTrapPowerSupplyRestored Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.

Variable	Description
<i>TrapPowerSupplyId</i>	ID of the power supply
<i>ChassisName</i>	The user assigned name for this chassis

2.1.6. nbsCmmcTrapFanFailure

Unique trap for fan failure events. This Notification should be of Severity WARNING.

Log message format: Chassis x Fan Failure, Fan Id: <FanId>

Table 2.11. nbsCmmcTrapFanFailure Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.12. nbsCmmcTrapFanFailure Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>TrapFanId</i>	ID of the fan
<i>ChassisName</i>	The user assigned name for this chassis

2.1.7. nbsCmmcTrapFanRestored

Sent when fan starts working again. This Notification should be of Severity WARNING.

Log message format: Chassis x Fan Restored, Fan Id: <FanId>

Table 2.13. nbsCmmcTrapFanRestored Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.14. nbsCmmcTrapFanRestored Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>TrapFanId</i>	ID of the fan
<i>ChassisName</i>	The user assigned name for this chassis

2.1.8. nbsCmmcTrapChassisTooHot

Sent when temperature rises above hottest permissible temperature. This Notification should be of Severity ERROR.

Log message format: Chassis x Too Hot, Chassis Temperature:
<ChassisTemperature> Chassis Temperature Limit:
<ChassisTemperatureLimit>

Table 2.15. nbsCmmcTrapChassisTooHot Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.16. nbsCmmcTrapChassisTooHot Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>ChassisTemperature</i>	The temperature (degrees Celsius) of the Chassis. Not supported value: 0x80000000
<i>ChassisTemperatureLimit</i>	The maximum safe temperature (degrees Celsius) of the Chassis. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis

2.1.9. nbsCmmcTrapChassisTooCold

Sent when temperature falls under coldest permissible temperature. This Notification should be of Severity ERROR.

Log message format: Chassis x Too Cold, Chassis Temperature:
<ChassisTemperature> Chassis Temperature Min:
<ChassisTemperatureMin>

Table 2.17. nbsCmmcTrapChassisTooCold Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.18. nbsCmmcTrapChassisTooCold Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>ChassisTemperature</i>	The temperature (degrees Celsius) of the Chassis. Not supported value: 0x80000000
<i>ChassisTemperatureMin</i>	The minimum safe temperature (degrees Celsius) of the Chassis. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis

2.1.10. nbsCmmcTrapChassisTempOk

Sent when temperature returns to permissible range. This Notification should be of Severity ERROR.

Log message format: Chassis x Temp Ok, Chassis Temperature:
<ChassisTemperature>

Table 2.19. nbsCmmcTrapChassisTempOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.20. nbsCmmcTrapChassisTempOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>ChassisTemperature</i>	The temperature (degrees Celsius) of the Chassis. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis

2.1.11. nbsCmmcTrapSlotModuleIn

Sent when card is physically inserted. This Notification should be of Severity ERROR.

Log message format: Slot x.x Module In, Slot Type: <SlotType>

Table 2.21. nbsCmmcTrapSlotModuleIn Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.22. nbsCmmcTrapSlotModuleIn Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotType</i>	The type of card in the slot. If the slot is empty and the chassis' color is black, this should be 0 or 1. If the slot is empty and the chassis' color is beige or gray, this should be 2. If a module is installed that the Agent does not support, this value should be 3. Values greater than 3 are used to indicate both the front panel and the functionality of the module.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.12. nbsCmmcTrapSlotModuleOut

Sent when card is physically removed. This Notification should be of Severity ERROR.

Log message format: Slot x.x Module Out, Slot Type: <SlotType>

Table 2.23. nbsCmmcTrapSlotModuleOut Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.24. nbsCmmcTrapSlotModuleOut Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotType</i>	The type of card in the slot. If the slot is empty and the chassis' color is black, this should be 0 or 1. If the slot is empty and the chassis' color is beige or gray, this should be 2. If a module is installed that the Agent does not support, this value should be 3. Values greater than 3 are used to indicate both the front panel and the functionality of the module.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.13. nbsCmmcTrapPortEnabled

Sent after nbsCmmcPortEnableOper changes to enable(3). This Notification should be of Severity WARNING.

Log message format: Port x.x.x Enabled

Table 2.25. nbsCmmcTrapPortEnabled Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.26. nbsCmmcTrapPortEnabled Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

Variable	Description
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.14. nbsCmmcTrapPortDisabled

Sent after nbsCmmcPortEnableOper changes to disable(2). This Notification should be of Severity WARNING.

Log message format: Port x.x.x Disabled

Table 2.27. nbsCmmcTrapPortDisabled Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.28. nbsCmmcTrapPortDisabled Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.15. nbsCmmcTrapPortLinkUp

Sent when nbsCmmcPortLink transitions from noSignal(2) to a connected state. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Link Changed, <PortLink>

Table 2.29. nbsCmmcTrapPortLinkUp Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLinkTraps</i>	Chassis	gen-trap link
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.30. nbsCmmcTrapPortLinkUp Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortLink</i>	The link status of the port.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.16. nbsCmmcTrapPortLinkDown

Sent when nbsCmmcPortLink transitions from a connected state to noSignal(2). This Notification should be of Severity ERROR.

Log message format: Port x.x.x Link Down

Table 2.31. nbsCmmcTrapPortLinkDown Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLinkTraps</i>	Chassis	gen-trap link
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.32. nbsCmmcTrapPortLinkDown Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.17. nbsCmmcTrapPortLINOn

Sent when Link Integrity Notification is turned on. This Notification should be of Severity WARNING.

Log message format: Port x.x.x LIN On

Table 2.33. nbsCmmcTrapPortLINOn Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLINTraps</i>	Chassis	gen-trap lin

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.34. nbsCmmcTrapPortLINOn Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.18. nbsCmmcTrapPortLINOff

Sent when Link Integrity Notification is turned off. This Notification should be of Severity WARNING.

Log message format: Port x.x.x LIN Off

Table 2.35. nbsCmmcTrapPortLINOff Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLINTraps</i>	Chassis	gen-trap lin
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.36. nbsCmmcTrapPortLINOff Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.19. nbsCmmcTrapPortLoopbackOn

Sent when Port is set to a Loopback state. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Loopback On

Table 2.37. nbsCmmcTrapPortLoopbackOn Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLoopbackTraps</i>	Chassis	gen-trap loopback
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.38. nbsCmmcTrapPortLoopbackOn Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.20. nbsCmmcTrapPortLoopbackOff

Sent when Port returns from a Loopback state. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Loopback Off

Table 2.39. nbsCmmcTrapPortLoopbackOff Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableLoopbackTraps</i>	Chassis	gen-trap loopback
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.40. nbsCmmcTrapPortLoopbackOff Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.21. nbsCmmcTrapPortMaximumExceeded

Sent when PortValue exceeds PortThreshold. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Maximum Exceeded, <PortThreshold> Port Value: <PortValue>

Table 2.41. nbsCmmcTrapPortMaximumExceeded Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.42. nbsCmmcTrapPortMaximumExceeded Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortValue</i>	Originally named nbsCmmcPortOpticalPower. Now usage may vary by card. For card 162, PortValue measures the Optical Power, or signal strength. For card 197, PortValue is a text string displaying signal strength in decibels. For cards 211 and 212, PortValue measures the current bandwidth level. Only one byte is used, and its value can be notSupported(1), under45Mbps(2), under155Mbps(3), under622Mbps(4), or under1Gbps(5)
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.22. nbsCmmcTrapPortRemoved

Sent when a hot-swappable port is removed. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Removed

Table 2.43. nbsCmmcTrapPortRemoved Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortChangeTraps</i>	Chassis	gen-trap port-change

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.44. nbsCmmcTrapPortRemoved Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.23. nbsCmmcTrapPortInserted

Sent when a hot-swappable port is inserted. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Inserted, <PortConnector> Port
 Wavelength: <PortWavelength>

Table 2.45. nbsCmmcTrapPortInserted Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortChangeTraps</i>	Chassis	gen-trap port-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.46. nbsCmmcTrapPortInserted Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortConnector</i>	The type of physical connector or jack.
<i>PortWavelength</i>	The output wavelength (in nanoMeters) of this transmitter. The reserved value -1 indicates that this object is not supported. This object has been superseded by nbsCmmcPortWavelengthX, which supports floating point wavelengths, and lists of wavelengths.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.24. nbsCmmcTrapPortTempTooLow

Sent when transmitter temperature is too cold. For SFF Digital Diagnostics, this corresponds to the low temperature alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Temp Too Low, <PortTemperature>
 <PortThreshold> <PortTemperatureLevel>

Table 2.47. nbsCmmcTrapPortTempTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.48. nbsCmmcTrapPortTempTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTemperature</i>	The temperature (in degrees celsius) of this trans- ceiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortTemperatureLevel</i>	This object indicates whether this port has a temperature problem. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate temperature is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate temperature is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate temperature is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related

Variable	Description
	object nbsCmmcPortTemperature indicates what the current temperature is.

2.1.25. nbsCmmcTrapPortTempTooHigh

Sent when transmitter temperature is too hot. For SFF Digital Diagnostics, this corresponds to the high temperature alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Temp Too High, <PortTemperature>
 <PortThreshold> <PortTemperatureLevel>

Table 2.49. nbsCmmcTrapPortTempTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.50. nbsCmmcTrapPortTempTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTemperature</i>	The temperature (in degrees celsius) of this trans- ceiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortTemperatureLevel</i>	This object indicates whether this port has a temperature problem. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate temperature is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate temperature is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is

Variable	Description
	ok(4). If Digital Diagnostics indicate temperature is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5). If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortTemperature indicates what the current temperature is.

2.1.26. nbsCmmcTrapPortRxPowerTooLow

Sent when received signal is too weak. For SFF Digital Diagnostics, this corresponds to the low RX power alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Rx Power Too Low, <PortRxPower>
<PortThreshold> <PortRxPowerLevel>

Table 2.51. nbsCmmcTrapPortRxPowerTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.52. nbsCmmcTrapPortRxPowerTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortRxPower</i>	The received optical power (in milli dBm) of this receiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortRxPowerLevel</i>	This object indicates whether this port has a problem with the power of its received signal. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate RxPower

Variable	Description
	is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate RxPower is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate RxPower is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortRxPower indicates what the current RxPower is.

2.1.27. nbsCmmcTrapPortRxPowerTooHigh

Sent when received signal is too powerful. For SFF Digital Diagnostics, this corresponds to the high RX power alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Rx Power Too High, <PortRxPower>
 <PortThreshold> <PortRxPowerLevel>

Table 2.53. nbsCmmcTrapPortRxPowerTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.54. nbsCmmcTrapPortRxPowerTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortRxPower</i>	The received optical power (in milli dBm) of this receiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000

Variable	Description
<i>PortRxPowerLevel</i>	This object indicates whether this port has a problem with the power of its received signal. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate RxPower is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate RxPower is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate RxPower is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortRxPower indicates what the current RxPower is.

2.1.28. nbsCmmcTrapPortTxPowerTooLow

Sent when transmitter power is too weak. For SFF Digital Diagnostics, this corresponds to the low TX power alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Tx Power Too Low, <PortTxPower>
 <PortThreshold> <PortTxPowerLevel>

Table 2.55. nbsCmmcTrapPortTxPowerTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.56. nbsCmmcTrapPortTxPowerTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTxPower</i>	The output power (in milli dBm) of this transmitter. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3),

Variable	Description
	speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortTxPowerLevel</i>	This object indicates whether this port has a problem with its transmitter power. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate TxPower is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate TxPower is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate TxPower is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5). If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortTxPower indicates what the current TxPower is.

2.1.29. nbsCmmcTrapPortTxPowerTooHigh

Sent when transmitter power is too strong. For SFF Digital Diagnostics, this corresponds to the high TX power alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Tx Power Too High, <PortTxPower>
 <PortThreshold> <PortTxPowerLevel>

Table 2.57. nbsCmmcTrapPortTxPowerTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.58. nbsCmmcTrapPortTxPowerTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTxPower</i>	The output power (in milli dBm) of this transmitter. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

Variable	Description
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortTxPowerLevel</i>	This object indicates whether this port has a problem with its transmitter power. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate TxPower is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate TxPower is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate TxPower is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5). If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortTxPower indicates what the current TxPower is.

2.1.30. nbsCmmcTrapPortAmpsTooLow

Sent when bias current is too small. For SFF Digital Diagnostics, this corresponds to the low bias current alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Amps Too Low, <PortBiasAmps>
<PortThreshold> <PortBiasAmpsLevel>

Table 2.59. nbsCmmcTrapPortAmpsTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.60. nbsCmmcTrapPortAmpsTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortBiasAmps</i>	The bias current (in microAmps) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis

Variable	Description
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortBiasAmpsLevel</i>	This object indicates whether this port has a problem with the electric current going through the port. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate BiasAmps is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate BiasAmps is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate BiasAmps is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortBiasAmps indicates what the current amperage is.

2.1.31. nbsCmmcTrapPortAmpsTooHigh

Sent when bias current is too large. For SFF Digital Diagnostics, this corresponds to the high bias current alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Amps Too High, <PortBiasAmps>
 <PortThreshold> <PortBiasAmpsLevel>

Table 2.61. nbsCmmcTrapPortAmpsTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.62. nbsCmmcTrapPortAmpsTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.

Variable	Description
<i>PortBiasAmps</i>	The bias current (in microAmps) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortBiasAmpsLevel</i>	This object indicates whether this port has a problem with the electric current going through the port. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate BiasAmps is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate BiasAmps is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate BiasAmps is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortBiasAmps indicates what the current amperage is.

2.1.32. nbsCmmcTrapPortVoltsTooLow

Sent when transceiver supply voltage is too low. For SFF Digital Diagnostics, this corresponds to the low supply voltage alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Volts Too Low, <PortSupplyVolts>
 <PortThreshold> <PortSupplyVoltsLevel>

Table 2.63. nbsCmmcTrapPortVoltsTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.64. nbsCmmcTrapPortVoltsTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortSupplyVolts</i>	The supply voltage (in milliVolts) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortSupplyVoltsLevel</i>	This object indicates whether this port has a problem with the electric voltage across the port. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate SupplyVolts is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate SupplyVolts is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate SupplyVolts is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortSupplyVolts indicates what the current supply voltage is.

2.1.33. nbsCmmcTrapPortVoltsTooHigh

Sent when transceiver supply voltage is too high. For SFF Digital Diagnostics, this corresponds to the high supply voltage alarm. This Notification should be of Severity ERROR.

Log message format: Port x.x.x Volts Too High, <PortSupplyVolts>
 <PortThreshold> <PortSupplyVoltsLevel>

Table 2.65. nbsCmmcTrapPortVoltsTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.66. nbsCmmcTrapPortVoltsTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortSupplyVolts</i>	The supply voltage (in milliVolts) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>PortThreshold</i>	Port Threshold - usage may be different for each card. For card 197, this indicates the minimum signal strength. Value ranges from -5 to -40 decibels. For card 211, valid values are: notSupported(1), speed45Mbps(2), speed155Mbps(3), speed622Mbps(4), speed1Gbps(5) For card 375, this indicates the rate limit and is expressed in units of Mbps. For cards 376 and 379, this indicates the rate limit and is expressed in units of Kbps. Not supported value: 0x80000000
<i>PortSupplyVoltsLevel</i>	This object indicates whether this port has a problem with the electric voltage across the port. If this port does not support SFF-8472 Digital Diagnostics, this value should be notSupported(1). If Digital Diagnostics indicate SupplyVolts is below the low Alarm Threshold, this value should be lowAlarm(2). If Digital Diagnostics indicate SupplyVolts is above the low Alarm Threshold but below the low Warning threshold, this value should be lowWarning(3). If Digital Diagnostics indicate this port is within the recommended operating range, value is ok(4). If Digital Diagnostics indicate SupplyVolts is higher than the high Warning threshold, but has not crossed the Alarm threshold, this value should be highWarning (5),. If Digital Diagnostics indicate this port has crossed the high Alarm threshold, this value should be highAlarm(6). The related object nbsCmmcPortSupplyVolts indicates what the current supply voltage is.

2.1.34. nbsCmmcTrapSwitchover

Sent when a self-healing (redundant ports) card switches traffic from an active port to a standby port. This Notification should be of Severity WARNING. The VARIABLE TrapLastMessage should specify the cause of the switchover, the PortName of the new Active port, and the PortName of the new Standby (formerly Active) port. The ChassisIndex and SlotIndex indicate the card that performed the switchover. The first PortIndex is the new Active port. The last PortIndex is the new Standby port. This trap should be accompanied by link up/down traps.

Log message format: Port x.x.x.x Switchover, Trap Port Name:
 <TrapPortName>

Table 2.67. nbsCmmcTrapSwitchover Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSwitchoverTraps</i>	Chassis	gen-trap switchover
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.68. nbsCmmcTrapSwitchover Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>TrapPortIndex</i>	Index of the Port
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>TrapPortName</i>	Name of the Port

2.1.35. nbsCmmcTrapSlotShuttingDown

Sent when the slot/card is shutting down. This Notification should be of Severity WARNING if the shutdown is deliberate, or ERROR if shutdown because of module failure, i.e. last gasp. The VARIABLE *nbsCmmcTrapShutdownReason* should specify the reason the card is shutting down. To enable/disable this notification, use the object *nbsCmmcChassisEnableModuleSpecificTraps*.

Log message format: Slot x.x Shutting Down, Shutdown Reason:
 <ShutdownReason>

Table 2.69. nbsCmmcTrapSlotShuttingDown Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.70. nbsCmmcTrapSlotShuttingDown Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>TrapShutdownReason</i>	The reason for the last system shutdown
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.36. nbsCmmcTrapPortCrcError

Sent when CRC Error is received on this port. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Crc Error

Table 2.71. nbsCmmcTrapPortCrcError Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.72. nbsCmmcTrapPortCrcError Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.37. nbsCmmcTrapCpeInManagedChassis

Sent when a module configured for customer premises is detected in a managed (central office) chassis. This Notification should be of Severity WARNING. To enable/disable this notification, use the object nbsCmmcChassisEnableModuleSpecificTraps.

Log message format: Slot x.x Cpe In Managed Chassis

Table 2.73. nbsCmmcTrapCpeInManagedChassis Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.74. nbsCmmcTrapCpeInManagedChassis Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis

Variable	Description
<i>SlotName</i>	The user assigned name for this slot.

2.1.38. nbsCmmcTrapCoWithoutCpe

Sent when a central office module has no link to a CPE module. This Notification should be of Severity WARNING. To enable/disable this notification, use the object *nbsCmmcChassisEnableModuleSpecificTraps*.

Log message format: Slot x.x Co Without Cpe

Table 2.75. nbsCmmcTrapCoWithoutCpe Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.76. nbsCmmcTrapCoWithoutCpe Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.39. nbsCmmcTrapCoTakesControl

Sent when a central office module begins active management of a dual-homed CPE module. This Notification should be of Severity WARNING. To enable/disable this notification, use the object *nbsCmmcChassisEnableModuleSpecificTraps*.

Log message format: Slot x.x Co Takes Control

Table 2.77. nbsCmmcTrapCoTakesControl Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.78. nbsCmmcTrapCoTakesControl Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.40. nbsCmmcTrapCoYieldsControl

Sent when a central office module ceases active management of a dual-homed CPE module. This Notification should be of Severity WARNING. To enable/disable this notification, use the object `nbsCmmcChassisEnableModuleSpecificTraps`.

Log message format: Slot x.x Co Yields Control

Table 2.79. nbsCmmcTrapCoYieldsControl Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.80. nbsCmmcTrapCoYieldsControl Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.41. nbsCmmcTrapCoLinkedToCo

Sent when one central office module is connected to another central office module. This Notification should be of Severity ERROR. To enable/disable this notification, use the object `nbsCmmcChassisEnableModuleSpecificTraps`.

Log message format: Slot x.x Co Linked To Co

Table 2.81. nbsCmmcTrapCoLinkedToCo Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.82. nbsCmmcTrapCoLinkedToCo Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.42. nbsCmmcTrapCpeFound

Sent when a remote CPE module is detected. This Notification should be of Severity WARNING. To enable/disable this notification, use the object `nbsCmmcChassisEnableModuleSpecificTraps`.

Log message format: Slot x.x Cpe Found

Table 2.83. nbsCmmcTrapCpeFound Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableModuleSpecificTraps</i>	Chassis	gen-trap module-specific
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.84. nbsCmmcTrapCpeFound Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.43. nbsCmmcTrapPortReflectionDetected

Sent when SingleFiber port detects its own signal reflecting back on itself. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Reflection Detected

Table 2.85. nbsCmmcTrapPortReflectionDetected Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.86. nbsCmmcTrapPortReflectionDetected Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.44. nbsCmmcTrapPortReflectionCeased

Sent when SingleFiber port no longer detects its own signal returning. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Reflection Ceased

Table 2.87. nbsCmmcTrapPortReflectionCeased Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.88. nbsCmmcTrapPortReflectionCeased Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.45. nbsCmmcTrapPortTempOk

Sent when transmitter temperature returns to normal. For Agent's internal severity-based filtering. The severity of this NOTIFICATION must match the severity of the nbsCmmcTrapPortTempTooLow or nbsCmmcTrapPortTempTooHigh NOTIFICATION that this overrides.

Log message format: Port x.x.x Temp Ok, <PortTemperature>

Table 2.89. nbsCmmcTrapPortTempOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.90. nbsCmmcTrapPortTempOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTemperature</i>	The temperature (in degrees celsius) of this trans- ceiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.46. nbsCmmcTrapPortRxPowerOk

Sent when received signal returns to normal. For Agent's internal severity-based filtering. The severity of this NOTIFICATION must match the severity of the nbsCmmcTrapPortRxPowerTooLow or nbsCmmcTrapPortRxPowerTooHigh NOTIFICATION that this overrides.

Log message format: Port x.x.x Rx Power Ok, <PortRxPower>

Table 2.91. nbsCmmcTrapPortRxPowerOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.92. nbsCmmcTrapPortRxPowerOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortRxPower</i>	The received optical power (in milli dBm) of this receiver. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.47. nbsCmmcTrapPortTxPowerOk

Sent when transmitter power returns to normal. For Agent's internal severity-based filtering. The severity of this NOTIFICATION must match the severity of the nbsCmmcTrapPortTxPowerTooLow or nbsCmmcTrapPortTxPowerTooHigh NOTIFICATION that this overrides.

Log message format: Port x.x.x Tx Power Ok, <PortTxPower>

Table 2.93. nbsCmmcTrapPortTxPowerOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.94. nbsCmmcTrapPortTxPowerOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.

Variable	Description
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortTxPower</i>	The output power (in milli dBm) of this transmitter. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.48. nbsCmmcTrapPortAmpsOk

Sent when bias current returns to normal. For Agent's internal severity-based filtering. The severity of this NOTIFICATION must match the severity of the nbsCmmcTrapPortAmpsTooLow or bsCmmcTrapPortAmpsTooHigh NOTIFICATION that this overrides.

Log message format: Port x.x.x Amps Ok, <PortBiasAmps>

Table 2.95. nbsCmmcTrapPortAmpsOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.96. nbsCmmcTrapPortAmpsOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortBiasAmps</i>	The bias current (in microAmps) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.49. nbsCmmcTrapPortVoltsOk

Sent when transceiver supply voltage returns to normal. For Agent's internal severity-based filtering. The severity of this NOTIFICATION must match the severity of the nbsCmmcTrapPortVoltsTooLow or nbsCmmcTrapPortVoltsTooHigh NOTIFICATION that this overrides.

Log message format: Port x.x.x Volts Ok, <PortSupplyVolts>

Table 2.97. nbsCmmcTrapPortVoltsOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortDiagsTraps</i>	Chassis	gen-trap port-diags
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.98. nbsCmmcTrapPortVoltsOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortSupplyVolts</i>	The supply voltage (in milliVolts) of this transmitter. The reserved value -1 indicates that this object is not supported.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.50. nbsCmmcTrapSlotTempTooLow

Sent when slot temperature is too cold. This Notification should be of Severity ERROR.

Log message format: Slot x.x Temp Too Low, Slot Temperature:
 <SlotTemperature>

Table 2.99. nbsCmmcTrapSlotTempTooLow Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.100. nbsCmmcTrapSlotTempTooLow Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotTemperature</i>	The temperature (in degrees celsius) of this slot. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.51. nbsCmmcTrapSlotTempTooHigh

Sent when slot temperature is too hot. temperature alarm. This Notification should be of Severity ERROR.

Log message format: Slot x.x Temp Too High, Slot Temperature:
<SlotTemperature>

Table 2.101. nbsCmmcTrapSlotTempTooHigh Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.102. nbsCmmcTrapSlotTempTooHigh Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotTemperature</i>	The temperature (in degrees celsius) of this slot. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.52. nbsCmmcTrapSlotTempOk

Sent when slot temperature returns to normal. This Notification should be of Severity ERROR.

Log message format: Slot x.x Temp Ok, Slot Temperature:
<SlotTemperature>

Table 2.103. nbsCmmcTrapSlotTempOk Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.104. nbsCmmcTrapSlotTempOk Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotTemperature</i>	The temperature (in degrees celsius) of this slot. Not supported value: 0x80000000
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.53. nbsCmmcTrapPortErrorsDetected

Sent when nbsCmmcPortErrorActivity changes to on(3). This Notification should be of Severity WARNING.

Log message format: Port x.x.x Errors Detected, Error Info:
<ErrorInfo>

Table 2.105. nbsCmmcTrapPortErrorsDetected Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.106. nbsCmmcTrapPortErrorsDetected Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>TrapErrorInfo</i>	Brief explanation of the cause or nature of errors that triggered an nbsCmmcTrapPortErrorsDetected trap.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.54. nbsCmmcTrapPortErrorsStopped

Sent when nbsCmmcPortErrorActivity changes to off(2). This Notification should be of Severity WARNING.

Log message format: Port x.x.x Errors Stopped

Table 2.107. nbsCmmcTrapPortErrorsStopped Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnablePortTraps</i>	Chassis	gen-trap port
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.108. nbsCmmcTrapPortErrorsStopped Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

Variable	Description
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.55. nbsCmmcTrapChassisInsufficientPower

Sent when power on chassis changed to insufficient. This Notification should be of Severity ERROR.

Log message format: Chassis x Insufficient Power

Table 2.109. nbsCmmcTrapChassisInsufficientPower Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.110. nbsCmmcTrapChassisInsufficientPower Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>ChassisName</i>	The user assigned name for this chassis

2.1.56. nbsCmmcTrapChassisSufficientPower

Sent when power on chassis changed to sufficient. This Notification should be of Severity ERROR.

Log message format: Chassis x Sufficient Power

Table 2.111. nbsCmmcTrapChassisSufficientPower Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableChassisTraps</i>	Chassis	gen-trap chassis
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.112. nbsCmmcTrapChassisSufficientPower Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>ChassisName</i>	The user assigned name for this chassis

2.1.57. nbsCmmcTrapSlotModuleLocked

Sent when nbsCmmcSysLockTypes is enabled(3) and a card incompatible with a slot's locked configuration is inserted. This Notification should be of Severity ERROR.

Log message format: Slot x.x Module Locked, Slot Type: <SlotType>

Table 2.113. nbsCmmcTrapSlotModuleLocked Enables

SNMP MIB object	Node	CLI command
<i>ChassisEnableSlotChangeTraps</i>	Chassis	gen-trap slot-change
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.114. nbsCmmcTrapSlotModuleLocked Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>SlotType</i>	The type of card in the slot. If the slot is empty and the chassis' color is black, this should be 0 or 1. If the slot is empty and the chassis' color is beige or gray, this should be 2. If a module is installed that the Agent does not support, this value should be 3. Values greater than 3 are used to indicate both the front panel and the functionality of the module.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.

2.1.58. nbsCmmcTrapSelectLinkChanged

Sent when a redundant port in a self-healing card switches between active and standby. The last varbind, *nbsCmmcPortSelectLink*, indicates this port's new state. This notification should come in a pair -- one trap for the new active port, another for the new standby port. This Notification should be of Severity WARNING.

Log message format: Port x.x.x Select Link Changed, <PortSelectLink>

Table 2.115. nbsCmmcTrapSelectLinkChanged Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.116. nbsCmmcTrapSelectLinkChanged Variables

Variable	Description
<i>TrapLastMessage</i>	The last message sent by the system
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>ChassisName</i>	The user assigned name for this chassis
<i>SlotName</i>	The user assigned name for this slot.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object <i>ifAlias</i> .

Variable	Description
<i>PortSelectLink</i>	For ports in self-healing redundant groups, this object describes this port's redundant state. The value notSupported(1) indicates this object is unused for this port. The value standby(2) indicates that traffic is not currently routed through this port. The value active(3) indicates that this port is the selected channel for passing data traffic. This object may be used to choose which port in a redundant group is active. That selection may be overridden by the system as appropriate, such as the link going down, or a preferred port coming up. The values (4) through (6) are deprecated. They will no longer be reported by the Agent, and attempts to set them should be rejected with the SNMP error badValue(3).

2.1.59. nbsOsaTrapPortChannelAdded

Sent when optical spectrum analyser first detects a channel. This Notification should be of Severity ERROR.

Log message format: osa Port Channel Added, <ChannelBand> Channel
 Number: <ChannelNumber> Channel Frequency
 Nominal: <ChannelFrequencyNominal>

Table 2.117. nbsOsaTrapPortChannelAdded Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.118. nbsOsaTrapPortChannelAdded Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object nbsOsaChannelNumber. Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelFrequencyNominal</i>	The nominal frequency, in MHz, of this channel.

2.1.60. nbsOsaTrapPortChannelDropped

Sent when optical spectrum analyser stops detecting a channel. This Notification should be of Severity ERROR.

Log message format:

```
osa Port Channel Dropped, <ChannelBand> Channel  
Number: <ChannelNumber> Channel Frequency  
Nominal: <ChannelFrequencyNominal>
```

Table 2.119. nbsOsaTrapPortChannelDropped Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.120. nbsOsaTrapPortChannelDropped Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object nbsOsaChannelNumber. Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelFrequencyNominal</i>	The nominal frequency, in MHz, of this channel.

2.1.61. nbsOsaTrapPortRxPowerTooLow

Sent when RxPower is lower then the configured threshold. This Notification should be of Severity ERROR.

```
Log message format:  osa Port Rx Power Too Low, <ChannelBand> Channel
                     Number: <ChannelNumber> Channel Rx Power Min:
                     <ChannelRxPowerMin> Channel Rx Power Oper:
                     <ChannelRxPowerOper>
```

Table 2.121. nbsOsaTrapPortRxPowerTooLow Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.122. nbsOsaTrapPortRxPowerTooLow Variables

Variable	Description
<i>nbs0saChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbs0saChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by

Variable	Description
	this object, and the channel number is shown in the object <i>nbsOsaChannelNumber</i> . Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelRxPowerMin</i>	The user-specified minimum signal strength, in millidecibels (mdBm), of this channel.
<i>nbsOsaChannelRxPowerOper</i>	The last known signal strength, in millidecibels (mdBm), of this channel.

2.1.62. nbsOsaTrapPortRxPowerOK

Sent when RxPower is OK. This Notification should be of Severity ERROR.

Log message format: osa Port Rx Power OK, <ChannelBand> Channel
Number: <ChannelNumber> Channel Rx Power Oper:
 <ChannelRxPowerOper>

Table 2.123. nbsOsaTrapPortRxPowerOK Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.124. nbsOsaTrapPortRxPowerOK Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object <i>nbsOsaChannelNumber</i> . Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelRxPowerOper</i>	The last known signal strength, in millidecibels (mdBm), of this channel.

2.1.63. nbsOsaTrapPortRxPowerTooHigh

Sent when RxPower is higher then the configured threshold. This Notification should be of Severity ERROR.

Log message format: osa Port Rx Power Too High, <ChannelBand> Channel
Number: <ChannelNumber> Channel Rx Power Max:
<ChannelRxPowerMax> Channel Rx Power Oper:
<ChannelRxPowerOper>

Table 2.125. nbsOsaTrapPortRxPowerTooHigh Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.126. nbsOsaTrapPortRxPowerTooHigh Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object nbsOsaChannelNumber. Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelRxPowerMax</i>	The user-specified maximum signal strength, in millidecibels (mdBm), of this channel.
<i>nbsOsaChannelRxPowerOper</i>	The last known signal strength, in millidecibels (mdBm), of this channel.

2.1.64. nbsOsaTrapPortOSNRTooLow

Sent when OSNR is lower then the configured threshold. This Notification should be of Severity ERROR.

Log message format: osa Port OSNR Too Low, <ChannelBand>
Channel Number: <ChannelNumber> Channel OSNR
Min: <ChannelOSNRMin> Channel OSNR Oper:
<ChannelOSNROper>

Table 2.127. nbsOsaTrapPortOSNRTooLow Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.128. nbsOsaTrapPortOSNRTooLow Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object nbsOsaChannelNumber. Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelOSNRMin</i>	The user-specified minimum OSNR of this channel
<i>nbsOsaChannelOSNROper</i>	The last known OSNR, in permil, of this channel.

2.1.65. nbsOsaTrapPortOSNRok

Sent when OSNR is ok. This Notification should be of Severity ERROR.

Log message format: osa Port OSNRok, <ChannelBand> Channel
 Number: <ChannelNumber> Channel OSNR Oper:
 <ChannelOSNROper>

Table 2.129. nbsOsaTrapPortOSNRok Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.130. nbsOsaTrapPortOSNRok Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object nbsOsaChannelNumber. Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.

Variable	Description
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelOSNROper</i>	The last known OSNR, in permil, of this channel.

2.1.66. nbsOsaTrapPortOSNRTooHigh

Sent when OSNR is higher then the configured threshold. This Notification should be of Severity ERROR.

Log message format: osa Port OSNR Too High, <ChannelBand>
 Channel Number: <ChannelNumber> Channel OSNR
 Max: <ChannelOSNRMax> Channel OSNR Oper :
 <ChannelOSNROper>

Table 2.131. nbsOsaTrapPortOSNRTooHigh Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.132. nbsOsaTrapPortOSNRTooHigh Variables

Variable	Description
<i>nbsOsaChannelIfIndex</i>	The Mib2 ifIndex of the optical spectrum analyzer port
<i>ifAlias</i>	Name of the Port
<i>nbsOsaChannelBand</i>	The ITU grid labels DWDM channels with a letter 'band' and a numeric channel. Within this mib, the band is indicated by this object, and the channel number is shown in the object <i>nbsOsaChannelNumber</i> . Frequencies of at least 180100 GHz but less than 190100 GHz are considered the L spectrum, and frequencies of at least 190100 but less than 200100 GHz are considered the C spectrum. Frequencies evenly divisible by 100 GHz are designated with a 'C' or 'L' prepended to the channel number. Frequencies that are offset by 50 GHz are designated 'H' within the C spectrum, and 'Q' within the L spectrum.
<i>nbsOsaChannelNumber</i>	The channel number can be derived by extracting the two middle digits from the six digit frequency in GHz.
<i>nbsOsaChannelOSNRMax</i>	The user-specified maximum OSNR of this channel
<i>nbsOsaChannelOSNROper</i>	The last known OSNR, in permil, of this channel.

2.1.67. nbsMccLinkToggleTrapStart

Sent when *nbsMccLinkToggleGroupStatus* changes to running(3).

Log message format: toggle group Start

Table 2.133. nbsMccLinkToggleTrapStart Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.134. nbsMccLinkToggleTrapStart Variables

Variable	Description
<i>nbsMccLinkToggleGroupSlot</i>	The Mib2-like ifIndex, in ccss000 format, of the slot whose ports are to be toggled,
<i>ifAlias</i>	Name of the Port

2.1.68. nbsMccLinkToggleTrapStop

Sent when a toggle session terminates and nbsMccLinkToggleGroupStatus changes to idle(2).

Log message format: toggle group Stop

Table 2.135. nbsMccLinkToggleTrapStop Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.136. nbsMccLinkToggleTrapStop Variables

Variable	Description
<i>nbsMccLinkToggleGroupSlot</i>	The Mib2-like ifIndex, in ccss000 format, of the slot whose ports are to be toggled,
<i>ifAlias</i>	Name of the Port

2.1.69. nbsPrbsTrapGeneratorStarted

Sent when nbsPrbsGenStatus transitions to generating(4). This Notification should be of Severity INFO.

Log message format: Port x.x.x prbs Generator Started

Table 2.137. nbsPrbsTrapGeneratorStarted Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.138. nbsPrbsTrapGeneratorStarted Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.70. nbsPrbsTrapGeneratorStopped

Sent when nbsPrbsGenStatus transitions from generating(4). This Notification should be of Severity INFO.

Log message format: Port x.x.x prbs Generator Stopped

Table 2.139. nbsPrbsTrapGeneratorStopped Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.140. nbsPrbsTrapGeneratorStopped Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.71. nbsPrbsTrapCheckerStarted

Sent when an interface begins checking for a bitstream. This Notification should be of Severity INFO.

Log message format: Port x.x.x prbs Checker Started

Table 2.141. nbsPrbsTrapCheckerStarted Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.142. nbsPrbsTrapCheckerStarted Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.72. nbsPrbsTrapCheckerStopped

Sent when an interface stops checking for a bitstream. This Notification should be of Severity INFO.

Log message format: Port x.x.x prbs Checker Stopped, <CheckStatus>

Table 2.143. nbsPrbsTrapCheckerStopped Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.144. nbsPrbsTrapCheckerStopped Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.

Variable	Description
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>nbsPrbsCheckStatus</i>	Indicates whether this port is checking a bitstream. If notSupported(1), this port cannot check a test bitstream. If idle(2), this port is currently not checking a test bitstream. If syncIn(3), this port currently is checking a bitstream and is synchronized with the pattern specified in nbsPrbsCheckPatternIndex. If syncOut(4), this port currently is checking a bitstream and is out of synchronization with the pattern specified in nbsPrbsCheckPatternIndex. If error(5), this port currently is checking a bitstream and an unspecified error occurred in the checker. If errOverflow(6), the Error Counter reached its maximum and checking has been suspended. To clear this condition, user should set nbsPrbsCheckAction to stop(2). If gaveUp(7), the pattern checker was unable to synchronize and aborted.

2.1.73. nbsPrbsTrapCheckerOverflowed

Sent when nbsPrbsCheckStatus transitions to errOverflow(6). This event indicates that the checker was unable to continue and is now in a suspended state which requires a user to manually stop the checker. This Notification should be of Severity ERROR.

Log message format: Port x.x.x prbs Checker Overflowed

Table 2.145. nbsPrbsTrapCheckerOverflowed Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.146. nbsPrbsTrapCheckerOverflowed Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.

2.1.74. nbsPrbsTrapCheckerErrorDetected

Sent when nbsPrbsCheckErrors transitions from zero (0). This event indicates the first error was detected in the incoming bitstream. This Notification should be of Severity ERROR.

Log message format: Port x.x.x prbs Checker Error Detected, <CheckStatus>

Table 2.147. nbsPrbsTrapCheckerErrorDetected Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.148. nbsPrbsTrapCheckerErrorDetected Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>nbsPrbsCheckStatus</i>	Indicates whether this port is checking a bitstream. If notSupported(1), this port cannot check a test bitstream. If idle(2), this port is currently not checking a test bitstream. If syncIn(3), this port currently is checking a bitstream and is synchronized with the pattern specified in nbsPrbsCheckPatternIndex. If syncOut(4), this port currently is checking a bitstream and is out of synchronization with the pattern specified in nbsPrbsCheckPatternIndex. If error(5), this port currently is checking a bitstream and an unspecified error occurred in the checker. If errOverflow(6), the Error Counter reached its maximum and checking has been suspended. To clear this condition, user should set nbsPrbsCheckAction to stop(2). If gaveUp(7), the pattern checker was unable to synchronize and aborted.

2.1.75. nbsPrbsTrapCheckerStatusUpdate

This Notification periodically reports the status, error counts, and running time of the Checker process. This Notification should be of Severity INFO.

Log message format: Port x.x.x prbs Checker Status Update,
 <CheckStatus> Check Errors: <CheckErrors> Check
 Progress: <CheckProgress>

Table 2.149. nbsPrbsTrapCheckerStatusUpdate Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.150. nbsPrbsTrapCheckerStatusUpdate Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.

Variable	Description
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>nbsPrbsCheckStatus</i>	Indicates whether this port is checking a bitstream. If notSupported(1), this port cannot check a test bitstream. If idle(2), this port is currently not checking a test bitstream. If syncIn(3), this port currently is checking a bitstream and is synchronized with the pattern specified in nbsPrbsCheckPatternIndex. If syncOut(4), this port currently is checking a bitstream and is out of synchronization with the pattern specified in nbsPrbsCheckPatternIndex. If error(5), this port currently is checking a bitstream and an unspecified error occurred in the checker. If errOverflow(6), the Error Counter reached its maximum and checking has been suspended. To clear this condition, user should set nbsPrbsCheckAction to stop(2). If gaveUp(7), the pattern checker was unable to synchronize and aborted.
<i>nbsPrbsCheckErrors</i>	Indicates how many errors were detected during the last pattern checking session. The Agent should clear this counter to zero(0) when nbsPrbsCheckStatus changes from idle(2). While pattern checking, Agent may increase this counter as errors occur. Once nbsPrbsCheckStatus changes to idle(2), this counter should report the final error count. If errors were detected but the count is unknown, Agent should report the number 1.
<i>nbsPrbsCheckProgress</i>	Indicates how long, in seconds, the port has been checking a bitstream. When nbsPrbsCheckStatus changes to idle(2), this.counter should be cleared to zero(0) and then increment once each second. When nbsPrbsCheckStatus changes to syncIn(3) or syncOut(4), this.counter should be frozen at its then current value.

2.1.76. nbsPrbsTrapCheckerSyncIn

Sent when a checker port synchronizes with a bitstream. This Notification should be of Severity ERROR.

Log message format: Port x.x.x prbs Checker Sync In, <CheckStatus>

Table 2.151. nbsPrbsTrapCheckerSyncIn Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.152. nbsPrbsTrapCheckerSyncIn Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.

Variable	Description
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>nbsPrbsCheckStatus</i>	Indicates whether this port is checking a bitstream. If notSupported(1), this port cannot check a test bitstream. If idle(2), this port is currently not checking a test bitstream. If syncIn(3), this port currently is checking a bitstream and is synchronized with the pattern specified in nbsPrbsCheckPatternIndex. If syncOut(4), this port currently is checking a bitstream and is out of synchronization with the pattern specified in nbsPrbsCheckPatternIndex. If error(5), this port currently is checking a bitstream and an unspecified error occurred in the checker. If errOverflow(6), the Error Counter reached its maximum and checking has been suspended. To clear this condition, user should set nbsPrbsCheckAction to stop(2). If gaveUp(7), the pattern checker was unable to synchronize and aborted.

2.1.77. nbsPrbsTrapCheckerSyncOut

Sent when a checker port loses synchronization with a bitstream. This Notification should be of Severity ERROR.

Log message format: Port x.x.x prbs Checker Sync Out, <CheckStatus>

Table 2.153. nbsPrbsTrapCheckerSyncOut Enables

SNMP MIB object	Node	CLI command
<i>SysEnableModuleTraps</i>	Config	snmp-server traps module

Table 2.154. nbsPrbsTrapCheckerSyncOut Variables

Variable	Description
<i>ChassisIndex</i>	The index of the Chassis.
<i>SlotIndex</i>	The slot index.
<i>PortIndex</i>	The index of the Port in the Slot in the Chassis to which this port is connected.
<i>PortName</i>	The user assigned name for this port. This object is also used for the MIB2 object ifAlias.
<i>nbsPrbsCheckStatus</i>	Indicates whether this port is checking a bitstream. If notSupported(1), this port cannot check a test bitstream. If idle(2), this port is currently not checking a test bitstream. If syncIn(3), this port currently is checking a bitstream and is synchronized with the pattern specified in nbsPrbsCheckPatternIndex. If syncOut(4), this port currently is checking a bitstream and is out of synchronization with the pattern specified in nbsPrbsCheckPatternIndex. If error(5), this port currently is checking a bitstream and an unspecified error occurred in the checker. If errOverflow(6), the Error Counter reached its maximum and checking has been suspended. To clear this condition, user should set nbsPrbsCheckAction to

Variable	Description
	stop(2). If gaveUp(7), the pattern checker was unable to synchronize and aborted.

2.2. SNMP Set Reference

2.2.1. Configuration SNMP MIB Object CLI Reference

Table 2.155. Configuration Table

SNMP MIB object	CLI Command
<i>SysAPIAgent</i>	sys api-agent
<i>SysAdminBootpState</i>	ip interface dhcp
<i>SysAuditLog</i>	sys audit-log
<i>SysCountersState</i>	sys clear-counters
<i>SysDefaultGateway</i>	ip default-gateway
<i>SysDiscovery</i>	sys discovery
<i>SysEnableModuleTraps</i>	snmp-server traps module
<i>SysEnablePowerSupplyTraps</i>	snmp-server traps power-supply
<i>SysGratuitousArp</i>	ip gratuitous-arp
<i>SysGuiDebugLog</i>	sys gui-server debug-log
<i>SysGuiServer</i>	sys gui-server
<i>SysGuiServerPort</i>	sys gui-server port
<i>SysGuiVerboseWarnings</i>	sys gui-server verbose-warnings
<i>SysIpAddr</i>	ip interface
<i>SysLmp</i>	sys lmp
<i>SysLockTypes</i>	sys lock-types
<i>SysLogDebugMessages</i>	log debug
<i>SysLogNvLevel</i>	log level nvram
<i>SysLogNvSize</i>	log size nvram
<i>SysLogRunningLevel</i>	log level running
<i>SysLogTrapLevel</i>	log level trap
<i>SysLoginIdleTimeout</i>	sys idle-timeout
<i>SysPasswordStrengthChecking</i>	sys password-strength-checking
<i>SysScpServer</i>	ip scp-server
<i>SysSerialBaudRate</i>	sys serial baudrate
<i>SysSerialTerminalType</i>	sys serial terminal-type
<i>SysSnmpPortAdmin</i>	snmp-server port
<i>SysSnmpV1</i>	snmp-server v1
<i>SysSnmpV2c</i>	snmp-server v2c
<i>SysSnmpV3</i>	snmp-server v3
<i>SysSshPort</i>	ip ssh-server port
<i>SysSshServer</i>	ip ssh-server

SNMP MIB object	CLI Command
<i>SysTelnetPort</i>	ip telnet-server port
<i>SysTelnetServer</i>	ip telnet-server
<i>SysTftpHostIP</i>	sys tftp-host-ip
<i>SysTimeServer</i>	sys rdate-server
<i>SysTrapEntry</i>	snmp-server host
<i>SysVlanIDAdmin</i>	ip interface vlan-id
<i>SysWarnNonMrvPluggable</i>	sys warn-non-mrv-pluggable
<i>SysWebPort</i>	ip web-server port
<i>SysWebServer</i>	ip web-server
<i>nbsNtpEnable</i>	ntp
<i>nbsNtpServerEntry</i>	ntp-server host
<i>nbsRemoteAAAAacct</i>	aaa accounting
<i>nbsRemoteAAAAauthen</i>	aaa authentication
<i>nbsRemoteAAAProtocol</i>	aaa protocol
<i>nbsSyslogServerEntry</i>	log remote-server host
<i>sysContact</i>	snmp-server sys contact
<i>sysLocation</i>	snmp-server sys location

2.2.2. Chassis SNMP MIB Object CLI Reference

Table 2.156. Chassis Table

SNMP MIB object	CLI Command
<i>ChassisCountersState</i>	clear-counters
<i>ChassisEnableChassisTraps</i>	gen-trap chassis
<i>ChassisEnableLINTraps</i>	gen-trap lin
<i>ChassisEnableLinkTraps</i>	gen-trap link
<i>ChassisEnableLoopbackTraps</i>	gen-trap loopback
<i>ChassisEnableModuleSpecificTraps</i>	gen-trap module-specific
<i>ChassisEnablePortChangeTraps</i>	gen-trap port-change
<i>ChassisEnablePortDiagsTraps</i>	gen-trap port-diags
<i>ChassisEnablePortTraps</i>	gen-trap port
<i>ChassisEnableSlotChangeTraps</i>	gen-trap slot-change
<i>ChassisEnableSwitchoverTraps</i>	gen-trap switchover
<i>ChassisLoopbackTimeout</i>	loopback-timeout
<i>ChassisName</i>	description
<i>ChassisTemperatureLimit</i>	temperature-limit
<i>ChassisTemperatureMin</i>	temperature-min

2.2.3. Slot SNMP MIB Object CLI Reference

Table 2.157. Slot Table

SNMP MIB object	CLI Command
<i>SlotCountersState</i>	clear-counters
<i>SlotDebugCli</i>	debug-cli
<i>SlotDefGateway</i>	ip default-gateway
<i>SlotHoming</i>	homing
<i>SlotIPAddress</i>	ip interface
<i>SlotName</i>	description
<i>SlotOperationType</i>	operation-type
<i>SlotRedundancyAdmin</i>	redundancy
<i>SlotRefresh</i>	refresh
<i>SlotReset</i>	reset
<i>SlotRmTrace</i>	rm-trace
<i>SlotToggleRate</i>	toggle-rate
<i>nbsEusmSlotAccControlActionTag</i>	default acc-control tagged
<i>nbsEusmSlotAccControlActionUntag</i>	acc-control untag
<i>nbsEusmSlotCoSMode</i>	cos
<i>nbsEusmSlotDscpEgressMode</i>	dscp egress-mode
<i>nbsEusmSlotDscpIngressAf</i>	dscp ingress af
<i>nbsEusmSlotDscpIngressAllOther</i>	dscp ingress all-other
<i>nbsEusmSlotDscpIngressCs</i>	dscp ingress cs
<i>nbsEusmSlotDscpIngressEf</i>	dscp ingress ef
<i>nbsEusmSlotDscpIngressZeroDscp</i>	dscp ingress zero-dscp
<i>nbsEusmSlotDscpRemark</i>	dscp remark
<i>nbsEusmSlotIometrix</i>	iometrix
<i>nbsEusmSlotLgaAction</i>	lga stop
<i>nbsEusmSlotLinkAggrAdmin</i>	link-aggregation
<i>nbsEusmSlotManagementVid</i>	management-vid
<i>nbsEusmSlotPmAction</i>	pm stop
<i>nbsEusmSlotStormControlBroadcast</i>	storm-control broadcast
<i>nbsEusmSlotStormControlMulticast</i>	storm-control multicast
<i>nbsEusmSlotStormControlUnicast</i>	storm-control unicast
<i>nbsEusmSlotUserPortIRAdmin</i>	user-port-limit
<i>nbsMccLinkToggleGroupAction</i>	link-toggle-action
<i>nbsMccLinkToggleGroupCycles</i>	link-toggle-cycles
<i>nbsMccLinkToggleGroupDnRate</i>	link-toggle-down-rate
<i>nbsMccLinkToggleGroupUpRate</i>	link-toggle-up-rate

SNMP MIB object	CLI Command
<i>nbsMccLinkToggleTrapStartEmit</i>	link-toggle-trap-start-emit
<i>nbsMccLinkToggleTrapStopEmit</i>	link-toggle-trap-stop-emit
<i>nbsVlanControlMgmtVid</i>	mgmt-vid
<i>nbsVlanSlotMapsHeartbeat</i>	maps heartbeat
<i>nbsVlanSlotMapsMode</i>	maps-mode
<i>nbsVlanSlotMapsRxTimer</i>	maps rx-timer
<i>nbsVlanSlotMapsTxTimer</i>	maps tx-timer
<i>nbsVlanSlotMapsVid</i>	maps vid

2.2.4. Port SNMP MIB Object CLI Reference

Table 2.158. Port Table

SNMP MIB object	CLI Command
<i>mrveFmOamAdminState</i>	oam
<i>PortAging</i>	aging
<i>PortAmpOutputPwrAdmin</i>	amplifier output-power
<i>PortAutoNegAd</i>	auto-neg-adv hex
<i>PortAutoNegWait</i>	auto-neg-wait
<i>PortAutoNegotiation</i>	auto-negotiation
<i>PortCableLen</i>	cable-len
<i>PortCountersState</i>	clear-counters
<i>PortDuplex</i>	duplex
<i>PortEnableAdmin</i>	shutdown
<i>PortErrorSelect</i>	error-select
<i>PortFCRecvAdmin</i>	flow-control receive
<i>PortFCSendAdmin</i>	flow-control send
<i>PortFlowControl</i>	flow-control
<i>PortI2CSpeed</i>	i2c-speed
<i>PortLIN</i>	lin
<i>PortLinkMatch</i>	link-match
<i>PortLoopback</i>	loopback
<i>PortMDIPinoutAdmin</i>	mdi-pinout
<i>PortMappingType</i>	mapping-type
<i>PortName</i>	description
<i>PortNominalBitRate</i>	nominal-bit-rate
<i>PortPreambleLen</i>	preamble-len
<i>PortPreferred</i>	preferred
<i>PortRMChassis</i>	rm-chassis
<i>PortRMPort</i>	rm-port

SNMP MIB object	CLI Command
<i>PortRMSlot</i>	rm-slot
<i>PortRedundantTxMode</i>	redundant-tx-mode
<i>PortRefresh</i>	refresh
<i>PortRemoteLoopback</i>	loopback internal
<i>PortSelectLink</i>	select-link
<i>PortSniffer</i>	sniffer
<i>PortSpeed</i>	speed
<i>PortTermination</i>	termination
<i>PortThreshold</i>	threshold
<i>PortThresholdAction</i>	threshold-action
<i>PortToggleMode</i>	toggle-mode
<i>PortTransmitUnmapped</i>	shutdown-unmapped
<i>nbsEusmCableTestStatus</i>	cable-test
<i>nbsEusmPortSmartLoopbackAction</i>	loopback off
<i>nbsEusmPortVlanTagAction</i>	default vlan-tag
<i>nbsEusmTgaAction</i>	traffic-gen action
<i>nbsEusmTgaDaType</i>	default traffic-gen da
<i>nbsEusmTgaFrameCountType</i>	default traffic-gen frame-count
<i>nbsEusmTgaFrameSizeType</i>	default traffic-gen frame-size
<i>nbsEusmTgaInterPacketGap</i>	traffic-gen inter-packet-gap
<i>nbsEusmTgaPatternType</i>	default traffic-gen pattern
<i>nbsEusmTgaSaType</i>	default traffic-gen sa
<i>nbsEusmTgaTagType</i>	default traffic-gen tag
<i>nbsPrbsCheckAction</i>	pattern-check stop
<i>nbsPrbsCheckDuration</i>	pattern-check duration
<i>nbsPrbsCheckUpdateFreq</i>	pattern-check update-freq
<i>nbsPrbsGenAction</i>	pattern-gen stop
<i>nbsPrbsGenDuration</i>	pattern-gen duration
<i>nbsSffMsxHasSgmiiPhy</i>	sgmii
<i>nbsSigCondRamanPumpPwrAdmin</i>	pump-pwr
<i>nbsSlaLossGainAction</i>	lga stop
<i>nbsSlaPerfMonAction</i>	pm stop
<i>nbsSlaTrafficGenAction</i>	traffic-gen-10 action
<i>nbsSlaTrafficGenDaType</i>	default traffic-gen-10 da
<i>nbsSlaTrafficGenFrameCountType</i>	default traffic-gen-10 frame-count
<i>nbsSlaTrafficGenFrameSizeType</i>	default traffic-gen-10 frame-size
<i>nbsSlaTrafficGenInterPacketGap</i>	traffic-gen-10 inter-packet-gap
<i>nbsSlaTrafficGenPatternType</i>	default traffic-gen-10 pattern

SNMP MIB object	CLI Command
<i>nbsSlaTrafficGenSaType</i>	default traffic-gen-10 sa
<i>nbsSlaTrafficGenTagType</i>	default traffic-gen-10 tag
<i>nbsVlanFwdEgressTagAction</i>	egress-tag-action
<i>nbsVlanFwdIngressTagAction</i>	ingress-tag-action
<i>nbsVlanFwdPriority</i>	priority
<i>nbsVlanFwdVid</i>	vid
<i>nbsVlanFwdVidList</i>	vid-list
<i>nbsVlanPortAccControlActionTag</i>	default acc-control tagged
<i>nbsVlanPortAccControlActionUntag</i>	acc-control untag



**MRV Communications, Inc.
20415 Nordhoff Street
Chatsworth, CA 91311**

**Tel: 818-773-0900
Fax: 818-773-0906
<http://www.mrv.com>**
