



Product Highlight

- 10 Gigabit Ethernet (10GbE) Performance for the Entire Datacenter
- Standard CAT-6a Cabling with RJ45 Connectors
- Backward Compatibility with Existing 1000BASE-T Networks Simplifies the Transition to 10GbE
- Flexible I/O virtualization for port partitioning and quality of service (QoS) of up to 64 virtual ports
- Unified Networking Delivering LAN, iSCSI, and FCoE in One Low Cost CNA
- Industry First Dual-Port 10GBASE-T Adapter with Single-Chip Solution with Integrated MAC + PHY
- Reliable and proven 10 Gigabit Ethernet technology from Intel Corporation

PCI Express x8 Dual Port 10 Gigabit Copper Server Adapter (Intel X540 Based)

XEA-U28

10GBASE-T converged network adapter simplifies migration to 10GbE, provides iSCSI, FCoE, Virtualization, and Flexible Port Partitioning.

10 Gigabit for the Broad Market

The link is the latest innovation in Intel's leadership to drive 10 Gigabit Ethernet into the broader server market. This adapter hosts Intel's latest Ethernet silicon, the Intel Ethernet Controller X540, which is used by many OEMs as a single chip solution for LAN on Motherboard (LOM) to deliver 10 Gigabit Ethernet (10 GbE) on the latest server platforms.

10GBASE-T Simplifies the Transition to 10GbE

The XENYA XEA-U28 10GBase-T works with existing networks today. It works with legacy Gigabit Ethernet (GbE) switches and Cat 6A cabling. Install the XENYA XEA-U28 10GBase-T adapter into a server and the auto-negotiation between 1 GbE and 10GbE provides the necessary backwards compatibility that most customers require for a smooth transition and easy migration to 10

GbE. When time and budget allows, 10GBASE-T switches can be added any time to experience the full benefits of 10GbE.

10GBASE-T uses the copper twisted pair cables that are very familiar to IT professionals today. It is everything you know and love about 1000BASE-T. The knowledge, training and investment in BASE-T are preserved. 10GBASE-T is the easiest and most versatile 10 GbE and you can deploy it anywhere in your data center. Its flexible reach from 1 meter to 100 meters supports the latest network architectures including Top of Rack (ToR), Middle of Row (MoR), and End of Row (EoR).

10G Performance at Low Cost and Low Power

The XENYA XEA-U28 10GBase-T adapter is the lowest cost way to deploy 10 GbE in your data center today. The XENYA XEA-U28 uses low cost, Cat 6 and Cat 6A cabling. Chances are this cabling already exists in the data center.

A way for Intel to reduce cost and power is to integrate components into a single-chip solution. Of course, integration is what Intel does best. With the new Intel X540 Controller, the MAC and the PHY are integrated into a single-chip solution.

So, why is integration important

First, integration translates to lower power. A single-chip solution simply uses less power than two separate components.

This means no more active heat sink and reduces the per-port power consumption.

Second, integration also means lower cost per port. Manufacturing a single part costs less than two. When cabling is accounted for, cost efficiencies realized from a single part mean 10GBASE-T is the lowest cost media to deploy.

With lower cost and power, 10GBASE-T is ready for broad deployment. 10GBASE-T is an option for every rack and tower server in the data center. The wait for a low cost 10 GbE copper solution to broadly deploy 10 GbE to all corners of the data center is over. The XENYA XEA-U28 10GBase-T adapter provides bandwidth-intensive applications with highly affordable 10 GbE network performance and cost-effective RJ-45 connectivity for distances up to 100 meters.

Exciting New data Center usage Models

More than simply a 10x increase in performance, with 10GbE there are exciting new usage models that are now possible, including Unified Networking (iSCSI, FCoE and LAN), Virtualization (VMDq and SR-IOV), and now, Flexible Port Partitioning (FPP).

Flexible i/o Virtualization

Virtualization changes the way server resources are deployed and managed by running multiple applications and operating systems independently on a single server.

The XENYA XEA-U28 10GBase-T adapter includes Intel Virtualization Technology for connectivity (Intel VT-c) to deliver I/O virtualization and Quality of Service (QoS) features designed directly into the Intel X540 controller on the adapter. Intel I/O virtualization advances network connectivity models used in today's servers to more efficient models by providing FPP, multiple Rx/Tx queues, and on-controller QoS functionality that can be used in both virtual and non-virtual server deployments.

Flexible Port Partitioning (FPP)

By taking advantage of the PCI-SIG SR-IOV specification, Intel Ethernet products enable FPP. With FPP, virtual controllers can be used by the Linux host directly and/or assigned to virtual machines. FPP allows you to use the functionality of SR-IOV to assign up to 63 processes per port to virtual functions in Linux. This enables an administrator to partition their 10 GbE bandwidth across multiple processes, ensuring a QoS by giving each assigned process equal bandwidth. Network administrators may also rate-limit each of these services to control how much of the 10GbE pipe is available to each process.

Unified Networking

Unified Networking solutions on the XENYA XEA-U28 10GBase-T adapter let you combine the traffic of multiple data center networks like LAN and SAN onto a single efficient network fabric. You now have the choice of NFS, iSCSI, or Fibre Channel over Ethernet (FCoE) to carry both network and storage traffic at speeds of up to 10 Gbps. The XENYA XEA-U28 10GBase-T adapter combines support for all of these traffic types in one adapter at no additional cost and with no additional licensing fees for the adapter.

Intel's Unified Networking solutions are enabled through a combination of standard Intel Ethernet products along with trusted network protocols integrated in the operating systems. Thus, Unified Networking is available on every Server either through LAN-on-Motherboard (LOM) implementation or via an add-in Network Interface Card (NIC).

Intel has delivered high quality Ethernet products for over 30 years and our Unified Networking solutions are built on the original principles that made us successful in Ethernet:

Open Architecture integrates networking with the server, enabling IT managers to reduce complexity and overhead while enabling a flexible and scalable data center network.

Intelligent offloads lower cost and power while delivering the application performance that customers expect.

Proven Ethernet unified Networking is built on trusted Intel Ethernet technology, enabling customers to deploy FCoE or iSCSI while maintaining the quality of their traditional Ethernet networks.

iSCSI Simplifies SAN Connectivity

iSCSI uses Ethernet to carry storage traffic, extending the familiarity and simplicity of Ethernet to storage networking, without the need for SAN-specific adapters or switches. XENYA XEA-U28 is the easiest, most reliable, and most cost-effective way of connecting servers to iSCSI SANs.

Open FCoE Consolidates LANs and Legacy SANs

Intel's Open FCoE solution enables XENYA XEA-U28 (adapters and controllers) to support Fibre Channel payload encapsulated in Ethernet frames. There is no upgrade charge for Open FCoE on the adapter. Just as with iSCSI, now customers can easily connect to an FCoE network with Intel 10 GbE solutions.

For the first time, Open-FCoE is now supported on 10GBASE-T. As 10GBASE-T switches come to market enabled with FCoE support, the XENYA XEA-U28 is ready when you're ready. This enables you to use cost-effective 10GBASE-T for all your converged networking needs. The Open-FCoE architecture uses a combination of FCoE initiators in Microsoft Windows- and Linux- operating systems and in the VMware- ESXi hypervisor to deliver high-performance FCoE solutions using standard 10 GbE Ethernet adapters.

This approach enables IT managers to simplify the data center and standardize on a single adapter for LAN and SAN connectivity. The XENYA XEA-U28 is designed to fully offload the FCoE data path to deliver full-featured converged network adapter (CNA) functionality without compromising on power efficiency and interoperability.

Data Center Bridging (dCB) delivers Loss-less Ethernet

Conventional Ethernet does not guarantee successful data delivery, which is not acceptable for SAN traffic. Ethernet enhancements such as Data Center Bridging (DCB) overcome that limitation with technologies that guarantee loss-less delivery, congestion notification, priority-based flow control, and priority groups.

The combination of 10GbE and unified networking helps organizations overcome connectivity challenges and simplify the data center infrastructure. 10GbE provides a simple, well-understood fabric for virtualized data centers, one that helps reduce cost and complexity as the number of virtual machines continues to grow.

Key Features

Low Cost, Low Power, 10 Gigabit Ethernet (10GbE) Performance for the Entire Datacenter

Standard CAT-6a Cabling with RJ45 Connectors

Backward Compatibility with Existing 1000BASE-T Networks Simplifies the Transition to 10GbE

Flexible I/O virtualization for port partitioning and quality of service (QoS) of up to 64 virtual ports

Unified Networking Delivering LAN, iSCSI, and FCoE in One Low Cost CNA

Industry First Dual-Port 10GBASE-T Adapter with Single-Chip Solution with Integrated MAC + PHY

Reliable and proven 10 Gigabit Ethernet technology from Intel Corporation

General

Intel X540 controller

Low-profile

Load balancing on multiple CPUs

Remote boot iSCSI and FCoE

Support for most Network Operating Systems (NOS)

RoHS compliant, lead-free technology

I/O Features for Multi-core Processor Servers

MSI-X support

Low latency

Header Splits and Replication in Receive

Multiple Queues

Tx/Rx IP, SCTP, TCP, and UDP checksum offloading (IPv4, IPv6) capabilities

Tx TCP segmentation offload (IPv4, IPv6)

IPsec Offload

Compatible with x8 and x16 standard and low-profile

PCI Express- slots

Receive/Transmit Side Scaling for Windows- and

Scalable I/O for Linux- (IPv4, IPv6, TCP/ UDP)

RJ45 connections over CAT-6a cabling

Virtualization Features

VMDq

Next-Generation VMDq(64 queues per port)

PC-SIG SR-IOV Implementation (64 virtual functions per port)

IPv6 Offloading

Advanced Packet Filtering

VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags

Network Management

Wired for Management (WfM) baseline v2.0 enabled for servers

DMI 2.0 support, Windows Management Instrumentation (WMI) and SNMP

Remote Installation Services (RIS)

PXE 2.0 enabled through boot Read-Only Memory (ROM)

Adapter Product Features

Intel PROSet Utility for easy configuration and management

Intel Lead-free technology

Plug and play specification support

Full-height bracket installed; low- profile bracket included in package

Advanced Software Feature

Adapter fault tolerance (AFT)

Switch fault tolerance (SFT)

Adaptive load balancing (ALB)

Virtual Machine Load Balancing (VMLB)

Teaming support

IEEE 802.3ad (link aggregation control protocol)

PCIe Hot Plug-/Active peripheral

Component interconnect (PCI)

IEEE 802.1Q- VLANs

IEEE 802.3 2005- flow control support

Tx/RxIP,TCP,&UDP checksum offloading (IPv4,IPv6) capabilities(Transmission control protocol TCP),user datagram protocol(UDP), Internet protocol (IP)

IEEE 802.1p-

TCP segmentation large send offload

MSI-X supports Multiple Independent Queues

Interrupt moderation

IPv6 offloading

Network Operating Systems (NOS) Software Support

Windows- 7 (IA32 and X64)

Windows Server- 2008 (x64 and IPF)

Windows Server- 2008 Core (x64 and IPF)

Windows Server- 2008 R2 (x64 and IPF)

Windows Server 2008 R2 Core (x64 and IPF)

Linux- SLES 11 SP1

Microsoft Windows Server 2003-

Microsoft Vista-

SUSE- SLES 10- or later, Professional 9.2 or later

Microsoft Windows Virtual Server- 2005-

Red Hat Enterprise- 4- or later

FreeBSD- 5.x or later support

VMware- ESX 4.0/4.1, ESXi 5.0 support

Fedora-EFI- 1.1

E-mail: info@xenya.si

Web: www.xenya.si